


AURA®

DOOR BOTTOM SEAL

FITTING GUIDE 3503

AAS3503

LENGTH:



CONTENTS

- AAS3503 door bottom seal
- Silicone reversible gasket
- Bag of screws

TOOLS REQUIRED

- Tape measure
- Pencil or marker
- Saw (power/hack)
- Drill
- Screw driver
- Knife

For more information please call:

+44 (0)1626 834252

All rights reserved. No part of this fitting guide may be reproduced, stored in a retrieval system, or transmitted in any means, electronic, mechanical, photocopying, recording or otherwise without the written permission of Lorient Polyproducts Limited. © Lorient Polyproducts Ltd 2019

www.lorientgroup.com

+44 (0)1626 834252

Lorient Polyproducts Ltd
Endavour House
Parrax Road
Heathfield Ind Estate
Newton Abbot
Devon TQ12 6UD
United Kingdom



AAS3503
DOOR BOTTOM SEAL

INSTALLATION DETAIL

This product is designed to be surface mounted.

STEP 1

If the door is installed, remove from its hinges, lay door on its edge and firmly restrain.

STEP 2

Measure door width and cut the seal to suit, using a sharp knife for the silicone gasket and a saw (power or hack) for the aluminium section.

STEP 3

Measure and mark out the seal position along the centre line of the door bottom.

STEP 4

Remove the silicone gasket and screw fix the aluminium section onto the door bottom using the screws supplied (fixing holes are pre-drilled).

STEP 5

Replace silicone gasket to form “U” section with fins facing outwards or inwards for a smooth external aspect. Note: the silicone gasket simply slides back into the profile.

TIP: Using talc can help to slide the gasket into the aluminium carrier.

STEP 6

Ends of the aluminium channel may be centre punched to prevent gasket movement.

STEP 7

Re-hang the door.

NOTE

We recommend the AAS3503 door bottom seal be fitted with any AURA® or LAS threshold plate.

IMPORTANT

Ensure that the installation of this product does not impede the opening or closing of the door. It is recommended to check the adjustment of the door seal periodically to ensure the door assembly to which it is fitted, closes & latches properly.

DISCLAIMER

Recommendations as to methods, use of materials and construction details are based on the experience and knowledge of Lorient and are given in good faith as a general guide and service to designers, contractors and manufacturers. Lorient reserves the right to make alterations or delete installation detail without prior notice.