SSA ABLOY

FIRE, SMOKE + ACOUSTIC SEALS FOR DOOR ASSEMBLIES



We've been designing and manufacturing high performance sealing systems for over 45 years.

And we're passionate about the products we make. Our dedicated R&D and testing facilities rigorously put our sealing systems through their paces – enabling us to enhance product form and function. We've built a strong reputation for design innovation; and for producing the highest quality sealing systems embracing acoustic, smoke, fire and thermal containment; as well as accessibility.

Respected throughout the industry for our technical expertise, we play an active role in helping to shape standards and best practice. We believe in providing excellent levels of customer service; and are at our best working in partnership with you.





ICONS EXPLAINED

The following icons are used throughout this brochure to give clear and easy recognition of a particular seal's function or possible application. Use of the icons does not necessarily indicate that test evidence exists. Refer to product system specification for relevant test evidence, or please check with the Lorient Technical team.



Thermal containment

Weather



protection

www.lorientuk.com/acousticsearch Our Acoustic Search tool provides quick and easy access to a wide range of tested acoustic sealing systems on a variety of popular door constructions and configurations.

PRODUCT ILLUSTRATIONS

All dimensions in this brochure are in millimetres.

CONTENTS

01

02

Life Threatening Forces 03

04 Intumescent Sealing

05 Sealing Against Leakage

06 **Building Regulations**

07

08 Fire Door Rating

09

10

12 - 25Product Range

26

28 - 35

36 - 41

4

46 - 47 Colour Range

48 Acoustic & Fire Testing

51 Testing + Technical Services

52

54

56

58



LIFE THREATENING FORCES

On average 220 people are killed and 5,515 are injured* in fires each year in the UK alone. Many of the casualties are attributable to breathing the toxic products of combustion from a remote fire.



Design Needs and Regulatory Requirements

When fire breaks out in a building the threat is twofold. Firstly, there is the fire itself and the hot smoke generated in the immediate vicinity. Secondly, there is cold smoke which will spread rapidly through the building, threatening people and property some distance from the fire. The Building Regulations take both these threats into account, and supporting documents give criteria for how they can be managed. Details can be found in Approved Document B (England & Wales), Technical Booklet E (N Ireland), and Technical Handbook Section 2 (Scotland).

The Regulations require large buildings to be divided into smaller fire and smoke resistant 'compartments', to reduce the risk of damage to the building as a whole and also to save lives in the case of a fire. Building a fire resistant wall or floor to make a compartment is relatively simple. However, building design becomes much more complex when the compartments need to be linked in some way - essential to make the building usable. Every time an aperture is cut into one of the compartment boundaries (for example, to install a door in a fire resistant wall, or to pass ductwork through a wall or ceiling) the aperture must be filled with something that will preserve the fire and smoke integrity of the compartment.

That's the role of Lorient's products – to work with the surrounding elements of the building to preserve the integrity of the fire and smoke resistant compartments. England 2024. Source: Home Office 2025.

Our fire and smoke seals can be fitted into fire rated doors; our glazing products can be fitted into doors, screens or fire rated partitions; our air transfer grilles can be installed into doors, walls and ducts.

Fire and smoke protection products must be tested to prove their performance, and indeed, separate tests are required for fire and smoke. Our products are all extensively tested, and our test reports are freely available on request.



Call our Technical Services team

+44 (0) 1626 834252

www.lorientuk.com



HIGH PERFORMANCE SEALING SYSTEMS

Today's architectural door assembly is heavily dependent on sealing systems for its performance; be that fire, smoke, acoustic or thermal containment. In choosing the right sealing solution, it's essential to make sure it's compatible with the door assembly.





INTUMESCENT SEALING

Our intumescent fire seals and combined fire, smoke and acoustic seals consist of intumescent material encased in rigid PVC which, for the combined seals also provides the carrier for an acoustic and smoke seal.



Fin type seals prevent the passage of cold smoke

Combined seals provide an effective barrier to the passage of fire and hot smoke

The intumescent material used in the mainstream range of our seals is sodium silicate based. This material has been chosen for several reasons:

- it has been proven in many hundreds of fire tests, world-wide;
- it's renowned for its comprehensive spread of performance characteristics;
- it has demonstrated outstanding consistency, reliability and durability.

Cold smoke sealing

We offer a range of smoke seal profiles, which incorporate either a polypropylene brush pile; or elastomeric fins which offer durable, low-friction performance for ease of door operation, and enhanced smoke and acoustic protection. Our range of cold smoke seals include products which can be used to upgrade existing fire rated doors to provide protection against cold smoke and sound. Specially designed to overcome the problems described above, they can be retrofitted with minimal disruption to the door assembly. Our Batwing® seal is recommended for upgrading fire rated doors. Refer to page 24 for further details.

Sealing for thermal containment

Sealing for smoke also makes a positive contribution to thermal containment between spaces within a building, as well as for external doors; helping in the efficient energy management of a building.

Other considerations -Accessibility

Approved Document M (England and Wales), Technical Booklet R (N. Ireland) and Technical Handbook Section 4 (Scotland) specify the size and location for glazed vision panels in doors in various situations, in order to promote safety and accessibility. Visual contrast on the leading edge of doors is also included, as are opening and closing forces for ease of door operation, height of the threshold plate and door width requirements. In addition to providing acoustic insulation and fire/smoke protection, doors must allow free passage. It's crucial that the sealing system fitted to door assemblies has minimal effect on the opening and closing operation of the assembly.



SEALING AGAINST LEAKAGE

Interrupting a smoke or acoustic door seal at hinges or other ironmongery can seriously reduce its effectiveness, and may even mean that the regulatory requirements will not be met. That's why it's vital to ensure a continuous smoke seal all around the door.





Leakage at hinges

To provide a permanent barrier to smoke and sound it's essential that an effective smoke seal is maintained at the hinges (shown above on the right). If locks are also unprotected the door will not meet regulatory requirements.

Our products are designed to enable an effective smoke and acoustic seal to be maintained.

Leakage at the threshold

A study of smoke and sound behaviour clearly shows that it is not sufficient to seal only the tops and sides of doors. Both cold smoke and sound will transfer to an adjacent compartment through the gap at the threshold. We can supply a range of threshold seals which will provide protection against smoke and when coupled with an effective perimeter seal will meet the requirements of Approved Document E. BS 8214 a Code of Practice document referred to in Approved Document B (England) states that if a fire rated door has a gap of over 3mm at the threshold, then you should fit a threshold seal. It is very difficult to know before the door is installed whether the gap will be over or under 3mm, so we do always recommend fitting a threshold seal. Please call our Technical Services team on +44 (0) 1626 834252 for further information.

Other areas of potential smoke leakage

It's essential for glazed vision panels, air transfer grilles and other similar features of a door to be evaluated with regard to smoke leakage. Further information can be found in our following brochures entitled:

- Fire resistant glazing systems
- Fire + smoke resistant air transfer grilles
- Fire resistant door hardware protection.

Back of frame

If not suitably protected, the back of frame can present a risk in the case of a fire. The gap between the frame and wall should be filled with a suitable fire resistant material; we recommend using two LP2004 fire seals (as represented throughout this brochure), for the back of the frame. Further information can be found in BS 8214:2016 Timber-based fire door assemblies. Code of practice.



BUILDING REGULATIONS

The Building Regulations provide guidance as to the minimum building standards to be achieved. They reference the relevant British and European Standards defining the test requirements and performance of the fire door assembly or fire doorset.

There are several aspects of the Buildings Regulations that must be considered in conjunction with each other when specifying and installing fire resistant glazing systems. The regional variations of the Building Regulations:

ENGLAND	Approved Documents
WALES	Approved Documents
SCOTLAND	Technical Handbooks
N.IRELAND	Technical Booklets
IRELAND	Technical Documents

	ENGLAND	WALES	SCOTLAND	N.IRELAND	IRELAND
FIRE	Approved	Approved	Technical	Technical	Technical Guidance
	Document B	Document B	Handbook 2	Booklet E	Document B
ACOUSTICS	Approved	Approved	Technical	Technical	Technical Guidance
	Document E	Document E	Handbook 5	Booklet G	Document E
ACCESSIBILITY	Approved	Approved	Technical	Technical	Technical Guidance
	Document M	Document M	Handbook 4	Booklet R	Document M
VENTILATION	Approved	Approved	Technical	Technical	Technical Guidance
	Document F	Document F	Handbook 6	Booklet K	Document F
THERMAL	Approved	Approved	Technical	Technical	Technical Guidance
	Document L	Document L	Handbook 6	Booklet F	Document L
SECURITY	Approved Document Q	Approved Document Q	Technical Handbook 4	-	-



STANDARDS + REGULATIONS

The requirements for fire and smoke containment with regard to `means of escape' are contained in the following standards:

FIRE + SMOKE

STANDARD	TITLE
BS 476-20:1987	Fire tests on building materials and structures. Method for determination of the fire resistance of elements of construction (general principles)
BS 476-22:1987	Methods for determination of the fire resistance of non-loadbearing elements of construction
BS 476-31.1:1983	Fire tests on building materials and structures. Methods for measuring smoke penetration through doorsets and shutter assemblies. Method of measurement under ambient temperature conditions
BS EN 1634-3:2004	Fire resistance and smoke control tests for door and shutter assemblies, openable windows and elements of building hardware. Smoke control test for door and shutter assemblies
BS EN 1634-1: 2014+A1:2018	Fire resistance and smoke control tests for door and shutter assemblies, openable windows and elements of building hardware. Smoke control test for door and shutter assemblies
BS 8214:2016	Timber-based fire door assemblies. Code of practice
BS 9999:2017	Fire safety in the design, management and use of buildings. Code of practice

ACOUSTIC

STANDARD	TITLE
BS EN ISO 10140-2:2010	Acoustics. Laboratory measurement of sound insulation of building elements - Measurement of airborne sound insulation
BS EN ISO 717-2:2020	Acoustics. Rating of sound insulation in buildings and of building elements. Impact sound insulation elements of construction
ASTM E413-16	Classification for Rating Sound Insulation



7

FIRE DOOR RATING

Fire doors are tested to BS 476-22 or BS EN 1634-1 to represent how they will function in a fire, and are rated in minutes and prefixed by the letters FD. The most common specification for fire doors leading to escape routes are fire doors resisting fire for 30 minutes, called FD30 fire doors.

BRITISH STANDARD: MINIMUM FIRE RESISTANCE (INTEGRITY) RATING	EUROPEAN STANDARD: MINIMUM FIRE RESISTANCE (INTEGRITY) RATING	NUMBER OF MINUTES THAT THE DOOR CAN RESIST FIRE
FD30	E30	30 minutes
FD60	E60	60 minutes
FD90	E90	90 minutes
FD120	E120	120 minutes

Sometimes doors are required to be both fire and smoke control (resistant) doors – tested to BS 476-31.1 or EN 1634-3. This means there will be either a combined fire and smoke seal; or a plain intumescent seal along with a separate smoke seal in either the entire perimeter of the door and/or in the frame.

If an air transfer grille (ATG) is required in a fire and smoke control door leaf, it should be fitted with an automatic smoke damper that will close if a fire breaks out.

The `S' suffix (e.g. FD30S) denotes that the door is both a fire and smoke controlled door.

BRITISH STANDARD: MINIMUM FIRE RESISTANCE (INTEGRITY) RATING	EUROPEAN STANDARD: MINIMUM FIRE RESISTANCE (INTEGRITY) RATING	NUMBER OF MINUTES THAT THE DOOR CAN RESIST FIRE + SMOKE
FD30S	E 30 S _a	30 minutes
FD60S	E 60 S _a	60 minutes
FD90S	E 90 S _a	90 minutes
FD120S	E 120 S _a	120 minutes



SOUND CONTAINMENT

Wherever noise influences human activity, effective acoustic sealing is essential. Whether preserving the confidentiality of discussions in a private office or doctor's surgery, or reducing noise from adjacent rooms in hotels; preservation of privacy is paramount. Legislation is in place that provides guidelines for acoustic performance of door assemblies in a number of situations.

ACOUSTIC RATING	LOCATION	REGULATIONS
29dB Rw	Dwelling houses, flats and rooms for residential purposes	Approved Document E
30dB Rw	Schools: all spaces except music rooms	Building Bulletin 93 "The Acoustic Design of Schools"
35dB Rw	School music rooms	Building Bulletin 93 "The Acoustic Design of Schools"



Approved Document E and Building Bulletin 93 for Schools



9

PRODUCT SELECTOR

We have a fantastic range of intumescent fire seals; most of the door seals are multi-functional and provide protection against fire, smoke and sound leakage. These seals are used in the top and vertical sides of door leaves, or in the frame. The bottom of the door should be sealed with a threshold seal from our architectural seals range.

Certification			Test evidence			ice		
PRODUCT	CERTIFIRE	BBA	IFC	UL	ø	<u>í</u>	((ه	PAGE
FINESSE™	CF330 + CF341	92/2841	FRPP454	-				16
DS SEAL	CF330 + CF341	92/2841	FRPP454	-				17
TS SEAL	CF330 + CF341	92/2841	FRPP454	-				18
AS SEAL	CF330 + CF341	92/2841	FRPP454	-				19
SS SEAL	CF330 + CF341	92/2841	FRPP454	-				20
FIRE SEAL	CF330 + CF341	92/2841	FRPP454	_				21
LAS1206	-	-	-	R27972				22
LAS1007	CF5179	-	-	R27972				23
LAS1010	CF5179	-	-	R27972				24
LAS1015	CF5179	-	-	R27972				24
LAS1212	CF5179	92/2841	-	R27972				24
LAS1206K	-	_	-	R27972				25
LAS1212K	CF5179	92/2841	-	R27972				26
LAS1011	CF5179	_	-	R27972				27
LAS1016	-	-	-	-				27





FINESSE™ SEALS



AS SEALS



BATWING®



LAS1011 FIRTREE®



DS SEALS



SS SEALS



SINGLE BATWING®



LAS1016 FIRTREE®



TS SEALS



FIRE SEAL



BATWING[®]-ON-A-STICK



11

FIRE, SMOKE + ACOUSTIC DOOR SEALS

Gaps around the four sides of a fire door leaf are essential – it's the only way the door can open and close. But these gaps create a point of weakness, where fire can take hold and destroy the door, and lethal smoke can pass through.

Lorient's intumescent seals protect those gaps. Most of the door seals shown in this section are multi-functional and provide protection against fire, smoke, sound leakage and heat loss. These seals are used in the top and vertical sides of door leaves, or in the frame. The bottom of the door should be sealed with a threshold seal from our architectural seals range.





INTUMESCENT SEALS

	FINESSE™	DS SEAL	TS SEAL	AS SEAL	SS SEAL	FIRE SEAL			
	A double-fin solution for fire, smoke & acoustic protection with superior aesthetics	A double-fin solution for fire, smoke & acoustic containment	A double-fin solution for fire, smoke & acoustic containment	A single-fin solution for fire, smoke & acoustic containment	A brush seal solution for fire & smoke containment	Intumescent fire seal for where no smoke sealing is required			
10 X 4MM SEALS	-	LP1004DS	LP1004TS	LP1004AS	LP1004SS	LP1004			
15 X 4MM SEALS	LP1504 Finesse™	LP1504DS	LP1504TS	LP1504AS	LP1504SS	LP1504			
20 X 4MM SEALS	LP2004 Finesse™	LP2004DS	LP2004TS	LP2004AS	LP2004SS	LP2004			
SMOKE SEAL MATERIAL	Elastomeric fins 4mm	Elastomeric fins 4mm	Elastomeric fins 4mm	Elastomeric fin 4mm	Polypropylene brush pile 4mm	-			
MIN / MAX GAP SIZES	3mm/4mm	3mm/4mm	3mm/4mm	3mm/4mm	3mm/4mm	3mm/4mm			
SEAL SIZES	All seals are available in standard lengths of 1m and 2.1m. Other lengths are available to special order. We can also produce fire seals ranging from 10mm – 70mm wide (non-standard, charges and lead times apply)								
FINISH	All our fire, smoke and acoustic seals are available in a range of standard and non-standard colours – see the colour details on pages 44 - 45								
FITTING	All our intumescent fire seals have a heavy duty self-adhesive backing. The adhesive used has been specially selected to provide excellent adhesion on a wide range of materials, including MDF on which it is usually difficult to obtain an effective bond. Make sure grooves are free from dust and grease. Lorient does not recommend oil or solvent based paint/primers								



FINESSE™ SEALS

LP1504 Finesse[™], LP2004 Finesse[™]

The Finesse[™] seal offers the ultimate in fire, smoke and acoustic protection. This high-class seal offers performance and durability with a truly superb appearance. With clear fins as standard, it's ideal for luxury installations, where aesthetics are paramount. The seal is available in a range of sizes to cover 30 and 60 minute applications.





SYSTEM SPECIFICATIONS

Test evidence

- Fire: BS 476-22:1987 & BS EN 1634-1:2008.
- Smoke: BS 476-31.1: 1983 at ambient
- temperature.
- Assessment: CNA/F14171.
- Acoustic: BS EN ISO 10140-2:2010.
- Durability: 100,000 cycles.

Characteristics

- Protects against fire, smoke, and sound.
- Low frictional resistance for ease of door operation.

Location

Single and double leaf doors.

Size

▶ 15 x 4mm, 20 x 4mm.

Use with

- Any architectural seals.
- Min/max gap size
- ▶ 3mm/4mm.

Seal material

PVC encased sodium silicate with flexible elastomeric fins.

Standard lengths

- ▶ 1m and 2.1m.
- Other lengths to special order.

Fixing

Heavy duty self-adhesive backing tape.

Finishes

- Black, white, dark brown, light brown and grey with clear fins as standard.
- Cream, red & silver are subject to MOQs and extended lead times.

Note: It's essential to consult the

manufacturer to determine exactly what configuration of seal & size of seal have been tested.

Certification



certifire (CF330 & CF341)





DS SEALS LP1004DS, LP1504DS, LP2004DS

Our DS door seal offers the ultimate in fire, smoke and acoustic protection. Its unique design means that whichever way round the product is installed, the seal can always be fitted in the correct place, maintaining the integrity of the acoustic + smoke seal at the ironmongery points. Available in a range of sizes to cover 30, 60, 90 and 120 minute applications.









FD30 example: DS seal offset to comply with Certifire CF341/330 (Shown with LAS8001 si)

SYSTEM SPECIFICATIONS

Test evidence

- Fire: BS 476-22:1987 & BS EN 1634-1:2008.
- Smoke: BS 476-31.1: 1983 at ambient
- temperature.
- Assessment: CNA/F14171.
- Acoustic: BS EN ISO 10140-2:2010.
- Durability: 100,000 cycles.

Characteristics

- Protects against fire, smoke, and sound.
- Low frictional resistance for ease of door operation.

Location

Single and double leaf doors.

Size

- 10 x 4mm, 15 x 4mm, 20 x 4mm.
- Other sizes available, please ask for details.

Use with

Any architectural seals.

Min/max gap size 3mm/4mm.

Seal material

 PVC encased sodium silicate with flexible elastomeric fins.

Standard lengths

- ▶ 1m and 2.1m.
- Other lengths to special order.

Fixing

Heavy duty self-adhesive backing tape.

Finishes

- Black, white, dark brown, light brown and grey with black fins as standard.
- Cream, red & silver are subject to MOQs and extended lead times.

FIRE, SMOKE + ACOUSTIC SEALS

FD60 example:

DS seal (Shown with LP1504 fire seal & LAS8001 si + cladding kit)

Note: It's essential to consult the manufacturer to determine exactly what configuration of seal & size of seal have been tested.

Certification



(CF330 & CF341)





TS SEALS LP1004TS LP1504TS, LP2004TS

Our TS door seal with double elastomeric fins offers fire, smoke and acoustic protection. Available in a choice of sizes to cover 30 and 60 minute applications.





LP2004TS



FD30 example: TS seal (Shown with Batwing® & LAS8001 si)

SYSTEM SPECIFICATIONS

Test evidence

- Fire: BS 476-22:1987 & BS EN 1634-1:2008.
- Smoke: BS 476-31.1: 1983 at ambient temperature.
- Assessment: CNA/F14171.
- Acoustic: BS EN ISO 10140-2:2010.
- Durability: 100,000 cycles.

Characteristics

- Protects against fire, smoke, and sound.
- Low frictional resistance for ease of door operation.

Location

Single and double leaf doors.

Size

- 10 x 4mm, 15 x 4mm, 20 x 4mm.
- Other sizes available, please ask for details.

- Use with
- Any architectural seals.

Seal material

- PVC encased sodium silicate with flexible elastomeric fins.
- Min/max gap size
- ▶ 3mm/4mm.

Fixing

Heavy duty self-adhesive backing tape.

Standard lengths

- ▶ 1m and 2.1m.
- Other lengths to special order.

Finishes

- Black, white, dark brown, light brown and grey with black fins as standard.
- Cream, red & silver are subject to MOQs and extended lead times.











-6

FD60 example:

TS seal (Shown with with LP1504 fire seal & LAS8001 si + cladding kit)

Note: It's essential to consult the manufacturer to determine exactly what configuration of seal & size of seal have been tested.

AS SEALS LP1004AS, LP1504AS, LP2004AS

Our AS door seal with elastomeric fin offers fire, smoke and acoustic protection. Available in a choice of sizes to cover 30 and 60 minute applications.





Fire, Smoke + Acoustic Door Seals

• Other sizes available, please

ask for details.

ASSA ABLOY

LORIENT

SS SEALS LP1004SS, LP1504SS, LP2004SS

Our SS door seal with polypropylene brush pile offers fire and smoke protection. Available in a choice of sizes to cover 30 and 60 minute applications.







FD30 example: SS seal (Shown with Batwing® & LAS8001 si)

SYSTEM SPECIFICATIONS

Test evidence

- Fire: BS 476-22:1987 & BS EN 1634-1:2008.
- Smoke: BS 476-31.1: 1983 at ambient temperature.
- Assessment: CNA/F14171.
- Durability: 100,000 cycles.

Characteristics

- Protects against fire and smoke.
- Low frictional resistance for ease of door operation.

Location

Single and double leaf doors.

Size

- 10 x 4mm, 15 x 4mm, 20 x 4mm.
- Other sizes available, please ask for details.

Use with

• Any architectural seals.

Min/max gap size

▶ 3mm/4mm.

Seal material

PVC encased sodium silicate with polypropylene brush pile.

Standard lengths

1m and 2.1m.

> Other lengths to special order.

Fixing

Heavy duty self-adhesive backing tape.

Finishes

- Black, white, dark brown, light brown and grey with black brush as standard.
- Cream, red & silver are subject to MOQs and extended lead times.

FD60 example:

 $\ensuremath{\text{SS seal}}$ (Shown with with LP1504 fire seal & LAS8001 si + cladding kit)

Note: It's essential to consult the manufacturer to determine exactly what configuration of seal & size of seal have been tested.

Certification



(CF330 & CF341)





FIRE SEALS

LP1004, LP1504, LP2004

Our intumescent fire door seals offer fire protection where no smoke sealing is required. Combine a fire seal with a Batwing[®] seal for acoustic and smoke containment. Available in a choice of sizes to cover 30 and 60 minute applications.





SYSTEM SPECIFICATIONS

Test evidence

- Fire: BS 476-22:1987 & BS EN 1634-1:2008.
- Assessment: CNA/F14171.

Characteristics

Protects against fire.

Location

Single and double leaf doors.

Size

- 10 x 4mm, 15 x 4mm, 20 x 4mm.
- Other sizes available, please ask for details.

Use with

> Any architectural seals.

Min/max gap size

▶ 3mm/4mm.

Seal material

- > PVC encased sodium silicate.
- Standard lengths
- ▶ 1m and 2.1m.
- Other lengths to special order.

Fixing

• Heavy duty self-adhesive backing tape.

Finishes

- Black, white, dark brown, light brown and grey as standard.
- Cream, red & silver are subject to MOQs and extended lead times.

Certification











LAS1206 Single Batwing®

FACE-FIXED

The LAS1206 Single Batwing[®] Seal is a smoke and acoustic perimeter seal. Its 10mm high, single fin design creates a tight seal while minimising the force required to open and close the door. Made from a flexible elastomeric material, the fin springs back into shape after every use, ensuring long-lasting performance. Easy to install with minimal disruption, the LAS1206 is suitable for both single and double leaf doors on the head and jambs.



LAS1206 Single Batwing®

> LAS1206 Single Batwing® Shown with fire seal as referenced in CNA/F14171 (also shown with LAS8001 si)

SYSTEM SPECIFICATIONS

Test evidence

- Smoke: BS 476-31.1: 1983 at ambient temperature.
- Acoustic: BS EN ISO 10140-2: 2010 (up to Rw 34dB).
- Durability: 100,000 cycles.

Characteristics

 Contributes towards sound, smoke, draught, and light containment.

Location

Head and jambs of single and double leaf doors.

Use with

> Any fire seals or architecturals seals.

Min/max gap size 3mm/4mm.

Seal material

 Co-extruded rigid back PVC with flexible fin.

Standard lengths

- 1m and 2.1m.
- Single doorset pack consisting of 1 x 1m and 2 x 2.1m.
- Other lengths to special order.

Fixing

Heavy duty self-adhesive backing tape.

Colours

- Black, white, dark brown, light brown and grey as standard.
- Silver, cream, red and clear are subject to MOQs.
- Note: clear Batwing[®] will not prevent light penetration.

Certification





LAS1007 Single Batwing®

FACE-FIXED

The LAS1007 Single Batwing[®] Seal is a smoke and acoustic perimeter seal for fire-rated steel-based door assemblies / doorsets. Its 14mm high, single fin design creates a tight seal while minimising the force required to open and close the door. Made from a flexible elastomeric material, the fin springs back into shape after every use, ensuring longlasting performance. Easy to install with minimal disruption, the LAS1007 is suitable for both single and double leaf doors on the head and jambs.







LAS1007 Single Batwing® Shown with LAS7001 si perimeter seal & LAS4014 si threshold plate

SYSTEM SPECIFICATIONS

Test evidence

- Smoke: BS 476-31.1: 1983 at ambient temperature; BS EN 1634-3:2004 at ambient temperature.
- Acoustic: BS EN ISO 10140-2: 2010 (up to Rw 34dB).
- Durability: 100,000 cycles.

Characteristics

- Contributes towards sound, smoke, draught, and light containment.
- Suitable for use on fire rated steel based door assemblies.

Location

 Head and jambs of single and double leaf doors.

Use with

Any fire seals or architecturals seals.

Min/max gap size

▶ 3mm/4mm.

Seal material

 Co-extruded rigid back PVC with flexible fin.

Standard lengths

- 1m and 2.1m.
- Single doorset pack consisting of 1 x 1m and 2 x 2.1m.
- Other lengths to special order.

Fixing

Heavy duty self-adhesive backing tape.

Colours

- Black, white, dark brown, light brown and grey as standard.
- Silver, cream, red and clear are subject to MOQs.
- Note: clear Batwing[®] will not prevent light penetration.

Certification



Certifire (CF5179) (LAS1007)

(CF51/9) (LAS1007)



LAS1010, LAS1212, LAS1015 Batwing[®]

FACE-FIXED

The LAS1010, LAS1212 & LAS1015 Batwing[®] smoke and acoustic seals are designed for easy installation with a simple peel and stick feature. The double fin design provides a reliable barrier against smoke and sound while minimising resistance when opening and closing the door.



Made from a flexible elastomeric material, the Batwing[®] seals boasts long-lasting performance as the fins spring back to their original shape after each use. Suitable for both single and double leaf doors on the head and jambs, this Batwing[®] seal installs with minimal disruption, offering a simple solution for smoke and acoustic containment.





LAS1212 Batwing®

Shown with fire seal as referenced in CNA/F14171 (also shown with LAS8001 si)

SYSTEM SPECIFICATIONS

Test evidence

- Smoke: BS 476-31.1: 1983 at ambient temperature; BS EN 1634-3:2004 at ambient and medium temperature (LAS1212); effective smoke seal up to 200°C.
- Acoustic: BS EN ISO 10140-2:2010 (up to Rw 44dB).
- Durability: 100,000 cycles.

Characteristics

 Contributes towards sound, smoke, draught, and light containment.

Location

 Head and jambs of single and double leaf doors.

Use with

- Any fire seals or architecturals seals.
- Min/max gap size

Seal material

 Co-extruded rigid back PVC with flexible fins.

Standard lengths

- 1m and 2.1m.
- Single doorset pack consisting of 1 x 1m and 2 x 2.1m.
- > Other lengths to special order.

Fixing

Heavy duty self-adhesive backing tape.

Colours

- Black, white, dark brown, light brown and grey as standard.
- Silver, cream, red and clear are subject to MOQs.
- Note: clear Batwing[®] will not prevent light penetration.

Certification

BBA

LAS1212







LAS1206K Batwing[®] on-a-stick

KERF-FIT

The LAS1206K Single Batwing®-on-a-stick is a smoke and acoustic seal designed for easy installation with its innovative kerf fixing feature. The single fin design provides a reliable barrier against smoke and sound while minimising resistance when opening and closing the door. Made from a flexible elastomeric material, the LAS1206K boasts long-lasting performance as the fin springs back to its after each use.







SYSTEM SPECIFICATIONS

Test evidence

- Smoke: BS 476-31.1: 1983 at ambient temperature.
- Acoustic: BS EN ISO 10140-2:2010 (up to Rw 37dB).
- Durability: 100,000 cycles.

Characteristics

 Contributes towards sound, smoke, draught, and light containment.

Location

 Head and jambs of single and double leaf doors.

Use with

> Any fire seals or architecturals seals.

Min/max gap size

▶ 3mm/4mm.

Seal material

Co-extruded rigid back PVC with flexible fins.

Standard lengths

- 1m and 2.1m.
- Single doorset pack consisting of 1 x 1m and 2 x 2.1m.
- > Other lengths to special order.

Fixing

- Push fit with kerf.
- ▶ Groove size for LAS1206K is 3mm x 11mm.

Colours

 Black, white, dark brown, light brown and grey as standard.

(also shown with LAS8001 si)

- Silver, cream, red and clear are subject to MOQs.
- Note: clear Batwing[®] will not prevent light penetration.

Certification







LAS1212K Batwing[®] on-a-stick

KERF-FIT

The LAS1212K Batwing®-on-a-stick is a smoke and acoustic seal designed for easy installation with its innovative kerf fixing feature. The 12mm profile, with a double fin design provides a reliable barrier against smoke and sound while minimising resistance when opening and closing the door.

●) <u>&</u> ★ ~

Made from a flexible elastomeric material, the LAS1212K boasts long-lasting performance as the fins spring back to their original shape after each use. Suitable for both single and double leaf doors on the head and jambs, this Batwing[®] seal installs with minimal disruption, offering a simple solution for smoke and acoustic containment.



LAS1212K Batwing® on-a-stick



LAS1212K Batwing[®] Shown with fire seal as referenced in CNA/F14171 (also shown with LAS8001 si)

SYSTEM SPECIFICATIONS

Test evidence

- Smoke: BS 476-31.1: 1983 at ambient temperature.
- Acoustic: BS EN ISO 10140-2:2010 (up to Rw 37dB).
- Durability: 100,000 cycles.

Characteristics

 Contributes towards sound, smoke, draught, and light containment.

Location

 Head and jambs of single and double leaf doors.

Use with

Any fire seals or architecturals seals.

Min/max gap size

▶ 3mm/4mm.

Seal material

 Co-extruded rigid back PVC with flexible fins.

Standard lengths

- 1m and 2.1m.
- Single doorset pack consisting of 1 x 1m and 2 x 2.1m.
- Other lengths to special order.

Fixing

- Push fit with kerf.
- ▶ Groove size for LAS1212K is 3mm x 9mm.

Colours

- Black, white, dark brown, light brown and grey as standard.
- Silver, cream, red and clear are subject to MOQs.
- Note: clear Batwing[®] will not prevent light penetration.

Certification

(R27972)

(CF5179)





PERIMETER SEALS

LAS1011 & LAS1016 Firtree™

KERF-FIT

Highly effective acoustic seals, which also provide additional cold smoke protection around the perimeter of fire rated doors. Flexible and durable. They can be fitted with minimal disruption to the door assembly.





FIRE, SMOKE + ACOUSTIC SEALS

CNA/F14171 (shown with LAS8005 si + LAS4002)

SYSTEM SPECIFICATIONS

Test evidence

- > Smoke: BS 476-31.1: 1983 at ambient temperature.
- Acoustic: BS EN ISO 10140-2:2010 (up to Rw 40dB).
- Durability: 100,000 cycles.

Characteristics

Protects against sound, smoke, draught and light.

Location

Head and jambs of single and double leaf doors. May also be used at the threshold when combined with a threshold plate.

Use with

> Any fire seals or architecturals seals.

Min/max gap size

- > 3mm/4mm (LAS1011).
- 4mm/6mm (LAS1016).

Seal material

Co-extruded rigid back PVC with flexible fins.

Standard lengths

• 1m and 2.1m. Other lengths to special order.

Fixing

Groove size is 3mm x 4mm.

Colours

- Black or white as standard.
- > Dark brown and light brown are subject to MOQs.

Certification

(VL) (R27972) LAS1011

BBA

LAS1011









APPLICATION DETAILS

The following pages show how our seals can be used to achieve the levels of protection against fire, smoke and sound required by Building Regulations and British Standard codes of practice.

The examples shown result from many years' experience and hundreds of fire, smoke and sound tests.

Our seals give equal performance whether placed in the door leaf or the frame, but it's preferable to fit them in the frame where they will not interfere with any size adjustments which may subsequently be made to the door leaf. However, it's essential to consult the manufacturer to determine exactly what configuration of seal has been tested.

A third party certificated timber doorset is the best guarantee that all elements, fire, smoke and acoustic seals, glazing and ironmongery are fully tested to the relevant standards.

The following illustrations are a selection of our recommended solutions for achieving fire protection of up to 60 minutes. However, it's possible to achieve fire protection beyond this level.

For more information on further solutions from our product range, please call our Technical Services team on +44 (0) 1626 834252.



Door configurations

Different door configurations need different sealing systems. That's because doors and seals work together, and different doors have different areas of strength and weakness that the seals need to complement.

Single leaf and double leaf doors behave very differently: you should never assume that a sealing system for single leaf doors will give the same performance on double leaf doors. Some common door configurations are shown below.

SINGLE LEAF DOORS

Single acting / hinged



Single acting / hinged Rebated / unrebated meeting stiles





APPLICATION DETAILS

	Door configuration				Sealing system Protecti					ection	n	
dB Rating	Fire Rating	Door	Thickness	Perimeter	Meeting Stile	Glazing Seal	Threshold	•())	<u>s</u>	ø		Page
30dB	FD30	Single	44mm	LAS1504DS	_	_	LAS8001 si LAS4002i				ID120	28
30dB	FD30	Single	44mm	LAS7001 si LP1504	_	_	LAS8001 si LAS4002				ID122	29
30dB	FD30	Single	44mm	LP1504 Finesse™	_	_	LAS8002 si				ID277	30
32dB	FD30	Single	44mm	LAS1212 LP1504	_	_	LAS8001 si LAS4011				ID415	31
31dB	FD30	Single	44mm	LAS1212 LP1504DS	_	System-36/7 PLUS	LAS8001 si				ID509	32
32dB	FD30	Single	44mm	LAS1212K LP1504DS	_	FF1	LAS8001 si				ID55	33
31dB	FD30	Double	44mm	LAS1212 LP1504	LP1004 x 2 LAS1011 x 2	_	LAS8002 si LAS4011				ID352	34
32dB	FD30	Double	44mm	LAS1212 LP1504 LP1504DS	LP1004DS LP1004	_	LAS8001 si LAS4011				ID436	35
33dB	FD60	Single	54mm	LP1504 Finesse™ LP1504	_	_	LAS8001 si with cladding kit				ID483	36
35dB	FD60	Single	54mm	LP1504DS x 2	_	_	LAS8001 si with cladding kit				ID602	37
35dB	FD60	Single	54mm	LAS1212 LP1504 LP1504DS	_	_	LAS8001 si with cladding kit				ID485	38
35dB	FD60	Single	54mm	LP1504DS LP1504	_	System-36/15 PLUS	LAS8001 si with cladding kit				ID68	39
32dB	FD60	Double	54mm	LAS1212 LP1504 LP1504DS	LP1504DS x 2 LAS9010 with cladding kit	RF1	LAS8001 si with cladding kit LAS4014 si				ID679	40
35dB	FD60	Double	54mm	LAS1212 LP1504 LP1504DS	LP1504DS x 2		LAS1016 x 2 LAS4014 si				ID156	41



Find acoustic solutions in our online Acoustic Search app: lorientuk.com/acousticsearch



30dB LP1504DS, LAS4002 & LAS8001 si

SINGLE LEAF | SINGLE SWING | 44MM | UNGLAZED | PARTICLE BOARD





	Product	Description	Key Features	Location	Performance		
1	LP1504DS	Combined fire, smoke & acoustic seal	 Low friction for ease of door operation Offers continuous smoke seal 	Jambs & head	Acoustic Smoke Fire Durability CERTIFIRE	BS EN ISO 10140-2:2010 BS 476-31.1:1983 BS 476-20/22:1987 BS EN 1634-1:2008 100,000 cycles CF341, CF330	
2	LAS4002	Low-profile slimline threshold plate	 Only 5mm high ideal for wheeled traffic Works with any threshold seal 	Threshold	UL R27972		
3	LAS8001 si	Drop seal	 Mechanism lifts the seal clear of the floor when opened Self-levelling works on uneven floors 	Threshold	Acoustic Smoke Fire Durability CERTIFIRE	BS EN ISO 10140-2:2010 BS 476-31.1:1983 BS EN 1634-3:2004 BS 476-20/22:1987 BS EN 1634-1:2008 100,000 cycles CF5179 UL R27972	
4	LP2004 (x2)	Fire seals	Easy to fit	Back of frame	Fire CERTIFIRE	BS 476-20/22:1987 BS EN 1634-1:2008 CF341, CF330	



30dB LAS7001 SI, LP1504, LAS4002 & LAS8001 si

SINGLE LEAF | SINGLE SWING | 44MM | 7MM PYRODUR PLUS | PARTICLE BOARD





Product		Description	Key Features	Location	Performance			
1	LAS7001 si	Perimeter seal	 Designed to be fitted to door stops 	Jambs & head	Acoustic Smoke Durability CERTIFIRE	BS EN ISO 10140-2:2010 BS 476-31.1:1983 100,000 cycles CF5179 UL R27972		
2	LP1504	Fire seal	Easy to fit	Jambs & head	Fire CERTIFIRE	BS 476-20/22:1987 BS EN 1634-1:2008 CF341, CF330		
3	LAS4002	Low-profile slimline threshold plate	 Only 5mm high ideal for wheeled traffic Works with any threshold seal 	Threshold	UL R27972			
4	LAS8001 si	Drop seal	 Mechanism lifts the seal clear of the floor when opened Self-levelling works on uneven floors 	Threshold	Acoustic Smoke Fire Durability CERTIFIRE	BS EN ISO 10140-2:2010 BS 476-31.1:1983 BS EN 1634-1:2014 + A1:2018 BS 476-20/22:1987 BS EN 1634-1:2008 100,000 cycles CF5179 UL R27972		
5	LP2004 (x2)	Fire seals	Easy to fit	Back of frame	Fire CERTIFIRE	BS 476-20/22:1987 BS EN 1634-1:2008 CF341, CF330		





30dB •

LP1504 Finesse[™] & LAS8002 si

SINGLE LEAF | SINGLE SWING | 44MM | UNGLAZED | PARTICLE BOARD





	Product	Description	Key Features	Location	Performan	ce
1	LP1504 Finesse™	Combined fire, smoke & acoustic seal	 Low friction for ease of door operation Offers continuous 	Jambs & head	Acoustic Smoke	BS EN ISO 10140-2:2010 BS 476-31.1:1983 BS 9999
			smoke seal		Fire	BS 476-20/22:1987 BS EN 1634-1:2008
					Durability	100,000 cycles
					CERTIFIRE	CF341, CF330
2	LAS8002 si	Drop seal	 Mechanism lifts the seal clear of the floor when opened 	Threshold	Acoustic Smoke	BS EN ISO 10140-2:2010 BS 476-31.1:1983 BS EN 1634-3:2004
			Self-levelling works		Durability	100,000 cycles
			on uneven floors		CERTIFIRE	CF5179 UL R27972
3	LP2004 (x2)	Fire seals	Easy to fit	Back of frame	Fire	BS 476-20/22:1987
					OFDIEIDE	BS EN 1634-1:2008
					CERTIFIRE	CF341, CF330





32dB LAS1212, LP1504, LAS4011 & LAS8001 si

SINGLE LEAF | SINGLE SWING | 44MM | UNGLAZED | PARTICLE BOARD





	Product	Description	Key Features	Location	Performan	ce
1	LAS1212 Batwing®	Smoke & acoustic perimeter seal	 Curved fin shape minimises open/ closing resistance Can be fitted with minimal disruption to door 	Jambs & head	Acoustic Smoke Durability CERTIFIRE	BS EN ISO 10140-2:2010 BS 476-31.1:1983 100,000 cycles CF5179 UL R27972
2	LP1504	Fire seal	 Easy to fit 	Jambs & head	Fire CERTIFIRE	BS 476-20/22:1987 BS EN 1634-1:2008 CF341, CF330
3	LAS4011	Low profile threshold plate	 Only 6mm high ideal for wheeled traffic Works with any threshold seal 	Threshold	UL R27972	
4	LAS8001 si	Drop seal	 Mechanism lifts the seal clear of the floor when opened 	Threshold	Acoustic Smoke	BS EN ISO 10140-2:2010 BS 476-31.1:1983 BS EN 1634-3:2004
			 Self-levelling works on uneven floors 		Fire	BS 476-20/22:1987 BS EN 1634-1:2008
					Durability CERTIFIRE	100,000 cycles CF5179 UL R27972
5	LP2004 (x2)	Fire seals	Easy to fit	Back of frame	Fire	BS 476-20/22:1987 BS EN 1634-1:2008
					CERTIFIRE	CF341, CF330





31dB

LAS1212, LP1504DS, System-36/7 PLUS & LAS8001 si

SINGLE LEAF | SINGLE SWING | 44MM | 7MM PYRODUR PLUS | FR ACOUSTIC CORE





	Product	Description	Key Features	Location	Performan	ce
1	LAS1212 Batwing®	Smoke & acoustic perimeter seal	 Curved fin shape minimises open/ closing resistance Can be fitted with minimal disruption to door 	Jambs & head	Acoustic Smoke Durability CERTIFIRE	BS EN ISO 10140-2:2010 BS 476-31.1:1983 BS EN 1634-3:2004 100,000 cycles CF5179 UL R27972
2	LP1504DS	Combined fire, smoke & acoustic seal	 Low friction for ease of door operation Offers continuous smoke seal 	Jambs & head	Acoustic Smoke Fire Durability CERTIFIRE	BS EN ISO 10140-2:2010 BS 476-31.1:1983 BS 476-20/22:1987 BS EN 1634-1:2008 100,000 cycles CF341, CF330
3	System-36/7 PLUS	Flexible U-shaped intumescent gasket for 30 minute fire resistant doors/ screens	 Suitable for use with range of standard fixing beads Flexible enough to be fitted to curved corners & circular vision panels 	Glazing seal	Fire Smoke CERTIFIRE Glass type	BS 476-20/22:1987 BS EN 1634-1:2008 CF5060 Pyrodur Plus 1700 x 300 x 7mm
4	LAS8001 si	Drop seal	 Mechanism lifts the seal clear of the floor when opened Self-levelling works on uneven floors 	Threshold	Acoustic Smoke Fire Durability CERTIFIRE	BS EN ISO 10140-2:2010 BS 476-31.1:1983 BS EN 1634-3:2004 BS 476-20/22:1987 BS EN 1634-1:2008 100,000 cycles CF5179 UL R27972
5	LP2004 (x2)	Fire seals	 Easy to fit 	Back of frame	Fire CERTIFIRE	BS 476-20/22:1987 BS EN 1634-1:2008 CF341, CF330



32dB LAS1212K, LP1504DS, FF1 & LAS8001 si

SINGLE LEAF | SINGLE SWING | 44MM | 7MM PYROGUARD | LAMINATED SOFTWOOD





	Product	Description	Key Features	Location	Performance	ce
1	LAS1212K Batwing®- on-a-stick	Smoke & acoustic perimeter seal	 Curved fin shape minimises open/ closing resistance Can be fitted with minimal disruption to door 	Jambs & head	Acoustic Smoke Durability CERTIFIRE	BS EN ISO 10140-2:2010 BS 476-31.1:1983 BS EN 1634-3:2004 100,000 cycles CF5179 UL R27972
2	LP1504DS	Combined fire, smoke & acoustic seal	 Low friction for ease of door operation Offers continuous smoke seal 	Jambs & head	Acoustic Smoke Fire Durability CERTIFIRE	BS EN ISO 10140-2:2010 BS 476-31.1:1983 BS 476-20/22:1987 BS EN 1634-1:2008 100,000 cycles CF341, CF330
3	FF1	A bead applied intumescent gasket for 30 minutes fire resistance	 Easy to install Design enables tolerances between door, bead & glass thicknesses to be accommodated 	Glazing seal	Fire CERTIFIRE Glass type	BS 476-20/22:1987 CF327 Pyroguard 1230 x 230 x 7.2mm
4	LAS8001 si	Drop seal	 Mechanism lifts the seal clear of the floor when opened Self-levelling works on uneven floors 	Threshold	Acoustic Smoke Fire Durability CERTIFIRE	BS EN ISO 10140-2:2010 BS 476-31.1:1983 BS EN 1634-3:2004 BS 476-20/22:1987 BS EN 1634-1:2008 100,000 cycles CF5179 UL R27972
5	LP2004 (x2)	Fire seals	Easy to fit	Back of frame	Fire CERTIFIRE	BS 476-20/22:1987 BS EN 1634-1:2008 CF341, CF330

LAS1212, LP1504, LP1004 x 2, LAS1011 x 2, LAS4012 & LAS8002 si

DOUBLE LEAF | SINGLE SWING | 44MM | UNGLAZED | PARTICLE BOARD



31dB



	Product	Description	Key Features	Location	Performan	ce
1	LAS1212 Batwing®	Smoke & acoustic perimeter seal	 Curved fin shape minimises open/ closing resistance Can be fitted with minimal disruption to door 	Jambs & head	Acoustic Smoke Durability CERTIFIRE	BS EN ISO 10140-2:2010 BS 476-31.1:1983 BS EN 1634-3:2004 100,000 cycles CF5179 UL R27972
2	LP1504	Fire seal	Easy to fit	Jambs & head	Fire CERTIFIRE	BS 476-20/22:1987 CF341, CF330
3	LP1004 (x2)	Fire seal	Easy to fit	Meeting stiles	As above	
4	LAS1011 Firtree® (x2)	Acoustic & smoke seal	 Flexible durable 4mm fins Easy to fit 	Meeting stiles	Acoustic Smoke Durability CERTIFIRE	BS EN ISO 10140-2:2010 BS EN 1634-3:2004 BS 476-31.1:1983 100,000 cycles CF5179 UL R27972
5	LAS4012	Low profile threshold plate	 Only 6mm high ideal for wheeled traffic Works with any threshold seal 	Threshold	UL R27972	
6	LAS8002 si	Drop seal	 Mechanism lifts the seal clear of the floor when opened Self-levelling works on uneven floors 	Threshold	Acoustic Smoke Fire Durability CERTIFIRE	BS EN ISO 10140-2:2010 BS 476-31.1:1983 BS EN 1634-3:2004 BS 476-20/22:1987 BS EN 1634-1:2008 100,000 cycles CF5179 UL R27972
7	LP2004 (x2)	Fire seals	Easy to fit	Back of frame	Fire	BS 476-20/22:1987 BS EN 1634-1:2008 CF341, CF330



32dB

LAS1212, LP1504DS, LP1004DS, LP1004, LAS4011 & LAS8001 si

DOUBLE LEAF | SINGLE SWING | 44MM | UNGLAZED | PARTICLE BOARD





	Product	Description	Key Features	Location	Performan	ce
1	LAS1212 Batwing®	Smoke & acoustic perimeter seal	 Curved fin shape minimises open/ closing resistance Can be fitted with minimal disruption to door 	Jambs & head	Acoustic Smoke Durability CERTIFIRE	BS EN ISO 10140-2:2010 BS 476-31.1:1983 BS EN 1634-3:2004 100,000 cycles CF5179 UL R27972
2	LP1504DS, LP1004DS	Combined fire, smoke & acoustic seal	 Exceptional low friction for ease of door operation Offers continuous smoke seal 	Jambs & head, meeting stiles (LP1004DS)	Acoustic Smoke Fire Durability CERTIFIRE	BS EN ISO 10140-2:2010 BS 476-31.1:1983 BS 476-20/22:1987 BS EN 1634-1:2008 100,000 cycles CF341, CF330
3	LP1004	Fire seal	Easy to fit	Meeting stiles	Fire CERTIFIRE	BS 476-20/22:1987 BS EN 1634-1:2008 CF341, CF330
4	LAS4011	Low profile threshold plate	 Only 6mm high ideal for wheeled traffic Works with any threshold seal 	Threshold	UL R27972	
5	LAS8001 si	Drop seal	 Mechanism lifts the seal clear of the floor when opened Self-levelling works on uneven floors 	Threshold	Acoustic Smoke Fire Durability CERTIFIRE	BS EN ISO 10140-2:2010 BS 476-31.1:1983 BS EN 1634-3:2004 BS 476-20/22:1987 BS EN 1634-1:2008 100,000 cycles CF5179 UL R27972
6	LP2004 (x2)	Fire seals	Easy to fit	Back of frame	Fire CERTIFIRE	BS 476-20/22:1987 BS EN 1634-1:2008 CF341, CF330



33dB

LP1504 Finesse[™], LP1504 & LAS8001 si with cladding kit

SINGLE LEAF | SINGLE SWING | 54MM | UNGLAZED | LAMINATED SOFTWOOD





	Product	Description	Key Features	Location	Performan	ce
1	LP1504 Finesse™	Combined fire, smoke & acoustic seal	 Low friction for ease of door operation Offers continuous smoke seal 	Jambs & head	Acoustic Smoke Fire Durability CERTIFIRE	BS EN ISO 10140-2:2010 BS 476-31.1:1983 BS 476-20/22:1987 BS EN 1634-1:2008 100,000 cycles CF341, CF330
2	LP1504	Fire seal	Easy to fit	Jambs & head	Fire CERTIFIRE	BS 476-20/22:1987 BS EN 1634-1:2008 CF341, CF330
3	LAS8001 si & cladding kit	Drop seal	 Mechanism lifts the seal clear of the floor when opened Self-levelling works on uneven floors 	Threshold	Acoustic Smoke Fire Durability CERTIFIRE	BS EN ISO 10140-2:2010 BS 476-31.1:1983 BS EN 1634-3:2004 BS 476-20/22:1987 BS EN 1634-1:2008 100,000 cycles CF5179 UL R27972
4	LP2004 (x2)	Fire seals	Easy to fit	Back of frame	Fire	BS 476-20/22:1987 BS EN 1634-1:2008 CF341, CF330



35dB LP1504DS x 2 & LAS8001 si with cladding kit

SINGLE LEAF | SINGLE SWING | 54MM | UNGLAZED | PARTICLE BOARD





	Product	Description	Key Features	Location	Performan	ce
1	LP1504DS (x2)	Combined fire, smoke & acoustic seal	 Low friction for ease of door operation Offers continuous smoke seal 	Jambs & head	Acoustic Smoke Fire Durability CERTIFIRE	BS EN ISO 10140-2:2010 BS 476-31.1:1983 BS 476-20/22:1987 BS EN 1634-1:2008 100,000 cycles CF341, CF330
2	LAS8001 si & cladding kit	Drop seal	 Mechanism lifts the seal clear of the floor when opened Self-levelling works on uneven floors 	Threshold	Acoustic Smoke Fire	BS EN ISO 10140-2:2010 BS 476-31.1:1983 BS EN 1634-3:2004 BS 476-20/22:1987 BS EN 1634-1:2008
					Durability CERTIFIRE	100,000 cycles CF5179 UL R27972
3	LP2004 (x2)	Fire seals	Easy to fit	Back of frame	Fire	BS 476-20/22:1987 BS EN 1634-1:2008
					CERTIFIRE	CF341, CF330





35dB LAS1212, LP1504, LP1504DS & LAS8001 si with cladding kit

SINGLE LEAF | SINGLE SWING | 54MM | UNGLAZED | LAMINATED SOFTWOOD





	Product	Description	Key Features	Location	Performan	ce
1	LAS1212* Batwing®	Smoke & acoustic perimeter seal	 Curved fin shape minimises open/ closing resistance Can be fitted with minimal disruption to door 	Jambs & head	Acoustic Smoke Durability CERTIFIRE	BS EN ISO 10140-2:2010 BS 476-31.1:1983 BS EN 1634-3:2004 100,000 cycles CF5179 UL R27972
2	LP1504*	Fire seal	Easy to fit	Jambs & head	Fire CERTIFIRE	BS 476-20/22:1987 BS EN 1634-1:2008 CF341, CF330
3	LP1504DS	Combined fire, smoke & acoustic seal	 Low friction for ease of door operation Offers continuous smoke seal 	Jambs & head	Acoustic Smoke Fire Durability CERTIFIRE	BS EN ISO 10140-2:2010 BS 476-31.1:1983 BS 476-20/22:1987 BS EN 1634-1:2008 100,000 cycles CF341, CF330
4	LAS8001 si with cladding kit	Drop seal	 Mechanism lifts the seal clear of the floor when opened Self-levelling works on uneven floors 	Threshold	Acoustic Smoke Fire Durability CERTIFIRE	BS EN ISO 10140-2:2010 BS 476-31.1:1983 BS EN 1634-3:2004 BS 476-20/22:1987 BS EN 1634-1:2008 100,000 cycles CF5179 UL R27972
5	LP2004 (x2)	Fire seals	Easy to fit	Back of frame	Fire CERTIFIRE	BS 476-20/22:1987 BS EN 1634-1:2008 CF341, CF330



35dB

LP1504DS, LP1504, System-36/15 PLUS & LAS8001 si with cladding kit

SINGLE LEAF | SINGLE SWING | 54MM | 15MM PYROSTOP | PARTICLE BOARD





	Product	Description	Key Features	Location	Performan	ce
1	LP1504DS	Combined fire, smoke & acoustic seal	 Low friction for ease of door operation Offers continuous smoke seal 	Jambs & head	Acoustic Smoke Fire Durability CERTIFIRE	BS EN ISO 10140-2:2010 BS 476-31.1:1983 BS 476-20/22:1987 BS EN 1634-1:2008 100,000 cycles CF341, CF330
2	LP1504	Fire seal	 Easy to fit 	Jambs & head	Fire CERTIFIRE	BS 476-20/22:1987 BS EN 1634-1:2008 CF341, CF330
3	System 36/15 PLUS	Flexible U-shaped intumescent gasket for 60 minute fire resistant doors and screens	 Suitable for use with range of standard fixing beads Flexible enough to be fitted to curved corners & circular vision panels 	Glazing seal	Fire Smoke CERTIFIRE Glass type	BS 476-20/22:1987 BS EN 1634-1:2008 CF5060 Pyrostop 1580 x 300 x 15mm
4	LAS8001 si with cladding kit	Drop seal	 Mechanism lifts the seal clear of the floor when opened Self-levelling works on uneven floors 	Threshold	Acoustic Smoke Fire Durability CERTIFIRE	BS EN ISO 10140-2:2010 BS 476-31.1:1983 BS EN 1634-3:2004 BS 476-20/22:1987 BS EN 1634-1:2008 100,000 cycles CF5179 UL R27972
5	LP2004 (x2)	Fire seals	 Easy to fit 	Back of frame	Fire CERTIFIRE	BS 476-20/22:1987 BS EN 1634-1:2008 CF341, CF330



LAS1212, LP1504, LP1504DS x 3, LAS9010 with cladding kit, LAS4014 si, LAS8001 si with cladding kit & RF1TM

DOUBLE LEAF | SINGLE SWING | 54MM | GLAZED | PARTICLE BOARD



	Product	Description	Key Features	Location	Performan	ce
1	LAS1212* Batwing®	Smoke & acoustic perimeter seal	 Curved fin shape minimises open/ closing resistance Can be fitted with minimal disruption to door 	Jambs & head	Acoustic Smoke Durability CERTIFIRE	BS EN ISO 10140-2:2010 BS 476-31.1:1983 BS EN 1634-3:2004 100,000 cycles CF5179 UL R27972
2	LP1504*	Fire seal	► Easy to fit	Jambs & head	Fire CERTIFIRE	BS 476-20/22:1987 BS EN 1634-1:2008 CF341, CF330
3	LP1504DS (x3)	Combined fire, smoke & acoustic seal	 Low friction for ease of door operation Offers continuous smoke seal 	Jambs & head, meeting stiles (LP1504DS x2)	Acoustic Smoke Fire Durability CERTIFIRE	BS EN ISO 10140-2:2010 BS 476-31.1:1983 BS 476-20/22:1987 BS EN 1634-1:2008 100,000 cycles CF341, CF330
4	LAS9010 with cladding kit	Flush bolt	 Seamlessly integrates with LAS8001 si drop seal Together they provide the ultimate system combining security, with acoustic, smoke and energy containment at the bottom of the door 	Meeting stiles	Acoustic Fire Durability Classified to	Maintains acoustic performance of drop seal 41dB (BS EN ISO 10140-1:2010+A2:2014, Annex J) BS 476-20/22:1987 BS EN 1634-1:2008 50,000 cycles o BS EN 12051:2000
5	LAS4014 si	Threshold plate	 Silicone gasket enhances acoustic containment 	Threshold	Acoustic UL	BS EN ISO 10140-2:2010 R27972
5	RF1 [™] with intumescent liner	Bead applied intumescent gaskets for 60 minutes fire resistance	 Easy to install Design enables tolerances between door, bead & glass thicknesses to be accommodated 	Glazing seal	Fire CERTIFIRE Glass type	BS 476-20/22:1987 CF5033 Pyroguard 1500 x 300 x 11mm
7	LAS8001 si with cladding kit	Drop seal	 Mechanism lifts the seal clear of the floor when opened Self-levelling works on uneven floors 	Threshold	Acoustic Smoke Fire Durability CERTIFIRE	BS EN ISO 10140-2:2010 BS 476-31.1:1983 BS EN 1634-3:2004 BS 476-20/22:1987 BS EN 1634-1:2008 100,000 cycles CF5179 UL R27972
8	LP2004 (x2)	Fire seals	► Easy to fit	Back of frame	Fire CERTIFIRE	BS 476-20/22:1987 BS EN 1634-1:2008 CF341, CF330

8





ARCHITECTURAL SEALS

The Lorient Architectural Seals range incorporates a variety of complementary door sealing systems including perimeter seals, drop seals, threshold plates, door bottom seals plus much more.



DROP SEALS

A range of Planet and Lorient drop seals that fit to the bottom of a door and drop down automatically when the door closes to form a firm seal. Suitable for a variety of door types including timber, metal, PVC, glass, sliding, and pivot doors.



PERIMETER SEALS

A comprehensive range of slimline perimeter seals for installation around the head, jambs and meeting stiles of doors.



THRESHOLD PLATES + RAMPS Threshold plates provide a firm and effective sealing surface for threshold seals to rest against, while also covering the join between different flooring materials.



DOOR BOTTOM SEALS A range of versatile and hardwearing door bottom seals, that seal the gap between the bottom of the door and the floor.



BRUSH SEALS

A series of hard-wearing sweep action brush seals suitable for numerous installations and door types; including single & double swing, revolving, sliding, up & over and roller shutter doors.



MAGNETIC SEALS

Magnetic seals for use on both steel and timber doors. These seals provide a tight seal for door jambs and may also be used as a stop.





MEETING STILE SEALS

A collection of robust seals designed for use on plain or rebated meeting stiles.



SPECIALITY SEALS

A range of speciality seals that features finger guards, a drip guard; and an innovative, slimline flush bolt that seamlessly integrates with our most popular drop seal - LAS8001 si.



COMPRESSION SEALS A variety of durable, flexible and lightweight seals that are easy to fit to the perimeter of timber doors and window frames.



GLASS DOOR SEALS Highly durable glass door seals for both the bottom of the door.



COLOUR RANGE

Our wide range of colours provides inspiration for all types of buildings; from luxurious and contemporary hotels, to bright and bold nurseries and schools - there's a perfect colour available to suit every project.

STANDARD COLOURS

Please note that the DS, TS, AS and SS profiles are supplied with black fins or brushes as standard. The Finesse™ profile is supplied with clear fins as standard.









BESPOKE FINISHES

We are also able to offer many special finishes and a precise colour matching service. Additional charges, minimum order quantities and extended lead times apply.

Note: The limitations of the printing process mean the colours shown here may not be exactly the same as the seals supplied. We can supply free mini samples to assist colour matching.



LIGHT REFLECTIVE VALUE

Light Reflectance Values (LRV), are a measure of the percentage of visible and usable light that is reflected from a surface when illuminated by a light source.

The values below have been determined with reference to the CIE LAB colour measurement method. The L co-ordinate represents lightness and extends from 0 (Black) to 100 (White) and has been used as a measure of light reflectance value.



Grey



CIE Y VALUE L* **A*** B* **BLACK** 4.76 27.39 -0.03 -0.9 **DARK BROWN** 8.61 35.15 35.15 35.15 RED 15.61 46.49 48.27 24.89 **LIGHT BROWN** 17.39 48.78 8.71 17.28 GREY 22.63 54.73 -0.73 -0.16 SILVER 27.49 59.28 -1.07 -2.3 57.65 CREAM 80.59 1.91 25.13 WHITE 86.03 94.24 -1.46 1.81



ACOUSTIC TESTING

The only way to determine the performance of a particular doorset design is to test that product, installed into a structure in a manner that replicates precisely the methods intended for use.



Acoustic Transmission Suite

How we test our products

We test the acoustic properties of each doorset and sealing system combination in an acoustic transmission suite in accordance with BS EN ISO 10140.

The test involves installing the assembly (door/window etc) within a dividing wall between a sound source room and a receiving room. Sound waves across the full frequency range are produced in the source room. The receiving room measures the sound pressure level. The difference between the sound pressure levels recorded in each room is determined as the Sound Reduction in index (R).

The Sound Reduction Index is an expression of the laboratory sound transmission performance of a particular element or construction. It is a function of the mass, thickness, sealing method and overall area of sample.

A series of tests will usually include measurement of a 'fully caulked' doorset. This is a test carried out using high density sealing (caulking) material to fill all gaps and provides a useful reference for the efficiency of a particular sealing system. Lorient test programmes are conducted with a range of common door cores, tested in real door scenarios, for example with an accepted industry gap size of 3-4mm. All Lorient sealing systems are acoustically tested in everyday operational mode and many are tested with long vision panels to meet the requirements of Approved Document M.

Rest assured that all information in this brochure has been derived from full size door assemblies.

A third party certificated timber doorset is the best guarantee that all elements – ironmongery, fire and smoke seals and glazing – are fully tested to the relevant standards.

For specialist doors and door blanks, it is essential to consult the manufacturer to determine which seals have been tested. Our Acoustic Search tool on our website provides quick and easy access to a wide range of tested acoustic sealing systems on a variety of popular door constructions and configurations.



FIRE TESTING

Fire and smoke protection measures are essential, life-saving precautions in a building. What's more, they protect the property from the devastating consequences of the fire itself, and the damaging effects of hot and cold smoke.

Fire and smoke protection products must be tested to prove their performance. Separate tests are required for fire and smoke.

Meeting the requirements

Fire resistance can be determined through destructive fire testing designed to replicate the product's intended end-use. Test evidence will be generated, demonstrating fire resistance performance to the required period of time (e.g. 30, 60, 90, 120 minutes).

The performance of a doorset must be considered as a complete unit i.e. the door leaf/leaves, frames, fire and smoke seals, vision panels and associated component parts, including door hardware.

Our fire, smoke and acoustic seals have been tested in accordance with British and European standards on a complete range of fire door configurations; single leaf, double leaf, single acting, double acting, latched and unlatched. This means that the door assembly will need to have several test reports:

- Fire resistance under the conditions of BS 476-22:1987;
 BS EN 1634-1:2014
- Smoke control under the conditions of BS 476-31.1:1983;
 BS EN 1634-3:2004
- Acoustic performance under the conditions of BS EN ISO 10140-2:2010, rated in accordance with BS EN ISO 717-1:2020.

The requirements for fire and smoke containment with regard to 'means of escape' are contained in the following documents; Approved Document B (England), Approved Document B (Wales), Technical Booklet E (N. Ireland), Technical Handbook Section 2 (Scotland).



Lorient Indicative Furnace

These documents specify that practically all internal fire resistant door assemblies are also required to prevent the passage of cold smoke.

Please bear in mind that performance in relation to cold smoke needs to be considered separately from performance in relation to fire and hot smoke, and a separate test report is required.

Third Party Certification

Lorient fire, smoke and acoustic seals are CERTIFIRE approved for use on

timber-based fire door assemblies. We also have British Board of Agrément, IFC and UL certification on a range of our seals.

If you require any further details, please contact our Technical Team via technical@lorientuk.com or call +44 (0) 1626 834252.





ASSA ABLOY

TESTING + TECHNICAL SERVICES

We've built our reputation on the quality and dependability of our products, and our investment in R&D has played a pivotal role in keeping our products at the forefront of our industry. Our dedicated Testing and Technical Services division has established itself as an important facility for manufacturers and designers of doors, windows, glazing systems and hardware, to name just a few.

TESTING SERVICES

Whether you're investigating new materials, or developing new or existing products, right through to durability testing and benchmarking performance – our team of experts will support you throughout the process. We are able to offer:

- Fire testing (indicative)
- ATG commissioning and maintenance for fire & smoke resisting air transfer grilles
- Mechanical cycling
- Environmental chamber analysis
- Attendance at external fire tests
- Consultancy services.



Lorient Indicative Furnace



CPDs

We offer five fully-accredited CPD seminars. Impartially presented by knowledgeable speakers, the seminars are structured to be technically informative, and provide practical advice.

The Importance of Fire Doors & Intumescent Seals

Fire doors and intumescent seals are critical components in fire safety, designed to prevent the spread of fire and smoke, saving lives and protecting property. This CPD explores their essential role in passive fire protection.

The CPD seminar covers:

- hard facts concerning deaths, injuries and property damage caused by fire and smoke;
- fire testing in the UK and the applicable fire and smoke leakage standards;
- how ironmongery affects fire doors and the vital role of intumescent protection;
- understanding intumescent seals for doors and the importance of third party certification;
- practical product solutions.

RIBA Core curriculum:

- Health, Safety & Wellbeing
- Legal, regulatory and statutory compliance

The Role and Performance of Fire & Smoke-Resisting Door Assemblies

The importance of fire and smoke resisting door assemblies is illustrated by the 220 fire related fatalities and 5,515 casualties in fires (England 2024). Apart from the human toll, property losses each year approach £2.52 billion.

The CPD seminar covers:

- hard facts concerning deaths, injuries and property damage caused by fire and smoke;
- regulatory requirements for fire and smoke resisting door assemblies;
- the nature and behaviour of smoke;
- effective design of door assemblies for smoke containment, including the threshold gap;
- design conflicts between fire containment, smoke containment, durability and ease of operation of the door;
- independent accreditation.

RIBA Core curriculum:

- Health, Safety & Wellbeing
- Legal, regulatory and statutory compliance
- Design, construction & technology



The Regulatory Reform (Fire Safety) Order 2005 & its implications for fire doors

The RRO consolidated 70 pieces of legislation; shifted responsibility for fire safety management; abolished the Fire Safety Certificate; established the Fire Risk Assessment and created major change in legal liability.

The CPD seminar covers:

- quick introduction to the RRO and who is responsible for a building's fire safety;
- examples of companies who have come under fire from the RRO;
- the dangers of fire and smoke;
- the importance of fire doors

 including installation and maintenance.
- examples of poorly maintained and fitted fire doors with cost effective solutions.
- independent accreditation.

RIBA Core curriculum:

- Health, Safety & Wellbeing
- Design, construction & technology

Five of our CPD seminars have been independently verified and certified by RIBA. A certificate for 1 hour's CPD will be provided, which contributes to Continuing Professional Development requirements.

50

www.lorientuk.com

Performance Door Design: The Basics of Sound Reduction

Effective acoustic containment helps to improve the quality of the built environment, preserving privacy as well as excluding unwanted noise. With changing regulations, it's essential to be informed of the relevant requirements and the implications for door assemblies.

The CPD seminar covers:

- the nature of sound, examining airborne transmission of sound;
- regulatory requirements and British Standards that relate to acoustic performance;
- test procedures and interpretation of test reports;
- effective design of door assemblies for acoustic performance, including door construction and the influence of sealing systems;
- design conflicts between acoustic performance, durability and ease of operation of the door;
- independent accreditation.

RIBA Core curriculum:

- Legal, regulatory and statutory compliance
- Design, construction & technology.

The Design & Specification of Intumescent Air Transfer Grilles

Intumescent air transfer grilles enable ventilation while ensuring fire protection. Under normal conditions, they allow airflow, but in a fire, they expand to block fire, hot smoke, and gases. Combined fire and smoke grilles are designed for cold smoke containment. Correct specification is critical to ensure effective fire protection and safety in building design.

The CPD seminar covers:

- an overview of fire and life safety principles as they relate to air transfer grilles;
- principals & performance of intumescent air transfer grilles and the critical role they play in passive fire protection;
- understanding effective cold smoke containment to save lives and protect property;
- guidance on specifying air transfer grilles that comply with regulatory and performance standards.
- Practical advice and solutions for optimal performance throughout the product lifecycle.

RIBA Core curriculum:

Design, construction & technology.

Each informative seminar provides an opportunity to keep up-to-date with all the latest facts about fire, smoke and acoustic containment, including regulations and standards – as well as exploring practical solutions.

All attendees will receive one-hour's CPD for each seminar.

If CPD certification is not required, presentations can be tailored to suit a wide variety of audiences, including client companies, building contractors, construction industry groups and trade associations.



To find out more or to book, contact us:

cpd@lorientuk.com

www.lorientuk.com



ADDITIONAL INFORMATION

TECHNICAL REFERENCES

Lorient is quality assured under the disciplines of BS EN ISO 9001:2015.

Accreditation to this standard is an assurance that we conduct our business to the complete satisfaction of our customers with regard to design solutions, manufacturing consistency and management procedures.

As a result, this internationally recognised standard for quality management generates customer confidence. Regular audits of our company procedures are undertaken by qualified BSI staff to ensure ongoing compliance with all aspects of the standard.



BS EN ISO 9001:2015 Certificate No. Q06104

Lorient has attained the

BS EN ISO 14001:2015 accreditation for environmental management. This internationally recognised standard shows that we have demonstrated our commitment to responsible environmental behaviour, including prevention of pollution, control and reduction of waste, and ongoing monitoring and improvement of our environmental performance. Achieving ISO 14001 is just one part of our ongoing commitment to operate in a sustainable way.



BS EN ISO 14001:2015 Certificate No. EMS 800254

FITTING INSTRUCTIONS

Comprehensive fitting instructions are available to download from our website **www.lorientuk.com**

MAINTENANCE

Periodic inspection/cleaning is recommended for all types of seals. The appearance and performance of brush seals will benefit from a wipe with a damp cloth at least once a year. Worn or damaged seals should be replaced without delay.

Further guidance is contained in the relevant sections of BS 8214:2016 "Code of practice for fire door assemblies".

HANDLING + STORAGE

No special precautions are required when handling our fire seals but they should always be treated with care and not bent or twisted. Safety data sheets are available on request. These products do not fall within the scope of COSHH regulations.

Our intumescent seals should be stored flat in a clean, dry, dust-free area away from heat and at a storage temperature of between 5°C and 40°C.

GUARANTEE OF ORIGIN

Each production batch of Lorient seals is identified unobtrusively on the edge of the profile with the Lorient name, product code reference, batch no., date of manufacture and third party accreditation. This ensures the product and details of its production can be traced should the need arise.

Unidentifiable substitute products should never be accepted.

MADE IN BRITAIN

We are proud to have been granted the prestigious Made in Britain marque for our products, designed and manufactured at our main facility in South West of the UK.



INTELLECTUAL PROPERTY

© 2025 ASSA ABLOY Ltd T/A Lorient. Lorient is a registered trade mark of ASSA ABLOY LIMITED in England.

This brochure is protected by copyright and neither the drawings nor the text may be reproduced or transmitted in any form without prior consent from Lorient. Lorient products described in this brochure are protected by patents and design registrations in Great Britain and other countries.

We are committed to continually enhancing and improving our product range. We reserve the right to change product specifications from time to time without prior notice. E&OE.

May 2025.



TRADE ASSOCIATIONS

Lorient is a member and active contributor to the following:









ACCREDITATIONS

BBA

BBA approvals provide independent assurance for the designer, specifier and end-user as to the 'fitness for purpose' of building products.



CERTIFIRE

Operated by Exova Warringtonfire, CERTIFIRE is an accredited independent product conformity scheme that requires products to meet the requirements of the tests, to add minimal resistance to opening and closing forces, to prove long term performance under a variety of service conditions, and to be permanently marked for easy identification.

certifire

IFC

IFC Certification Ltd is a UKAS approved and internationally recognised provider of third party Certification services – designed to give confidence to specifiers, users, occupiers, owners and enforcement bodies that products have been thoroughly and independently evaluated and will continue to be manufactured to the same specification as originally tested.



UL

UL is a global independent safety science company that tests a diverse range of products; representative samples of a product must be tested and meet UL's stringent requirements to carry the marque. These requirements are based primarily on UL's published and nationally recognised Standards for Safety. Businesses, consumers and regulatory authorities around the world recognise the trusted rigour and technical excellence of UL certifications. Lorient is proud to have achieved the UL Mark on many of its products. These are detailed on individual pages.





COMPREHENSIVE SUPPORT

As a company we have over 45 years' experience, so our experts are well equipped to listen, help and advise you on your sealing system requirements.

Technical Services

We're happy to provide specialist advice on acoustic, smoke and fire protection for refurbishment and new build projects. If you need assistance, you can call our Technical Services team.

Alternatively, we can arrange a site visit to get a clearer idea of your needs and how we can help you. We also provide copies of test reports and samples where needed; and can give guidance on how best to meet Building Regulations and Standards.

Web Support

Our website features a comprehensive range of supporting documents covering the entire range of products, including installation guides and CAD drawings. All of our brochures and products sheets are also available for download, together with copies of certification and specification texts.

Online Acoustic Search tool

Our Acoustic Search tool on our website gives you quick and easy access to a wide range of tested acoustic sealing systems on a variety of popular door constructions & configurations.

lorientuk.com/acousticsearch

The tool allows users to select a specific decibel rating; along with door configuration, fire door rating, doorset type etc to filter the results. The 'Acoustic Search' tool is updated frequently with Lorient's ever-expanding portfolio of test evidence. If you're looking for high performance or specialist applications – please contact us on +44 (0) 1626 834252, there may be some additional configurations we haven't yet published.



Customisation

If you have a particular requirement which isn't covered by the applications in this brochure, we may be able to supply an existing non-standard item, or even develop a customised solution for you. Utilising in-house expertise, bespoke products are created to your requirements; from a functional or aesthetic perspective, or both.

Lorient's dedicated Technical Services team supports and works as part of your design team, offering informed product advice and guidance on regulatory requirements and standards.

> Call our Technical Services team +44 (0) 1626 834252 www.lorientuk.com



SEALING SOLUTIONS

Detailed information about our products can be found in the following brochures:



Lorient Architectural Seals

A comprehensive range of innovative door sealing solutions—designed to improve performance and enhance aesthetics. The collection includes perimeter seals, drop seals, door bottom seals, threshold plates, and more - engineered for durability, efficiency, and seamless integration.

Fire, Smoke and Acoustic Seals for Door Assemblies

Our core range of high-performance fire, smoke and acoustic seals for door assemblies.

Planet Drop Seals

A versatile range of high-performance drop seals designed for acoustic, smoke, and fire containment. Suitable for timber, metal, PVC, and glass doors - including hinged, sliding, folding, and swing.

Fire and Smoke Resistant Air Transfer Grilles

A comprehensive range of intumescent fire-resistant and fire & smoke-resistant air transfer grilles for doors, walls, ducts, and floors.

Fire Resistant Door Hardware Protection

Letterplates, door edge protector and intumescent kits that can safely be installed into fire rated doors without compromising the fire/smoke performance.

Fire Resistant Glazing Systems

Fire resistant intumescent glazing systems for doors, screens and partitions.

Acoustic Sealing Systems for Door Assemblies

A comprehensive series of acoustic sealing systems for various types of door construction.

Copies of these brochures are available by calling +44 (0)1626 834252 or download from our website www.lorientuk.com



FAQS

I need to buy a 30 minute fire seal - which product should I buy?

First of all, please do remember that adding a fire seal to any door doesn't automatically make it a fire door. Do make sure that you have a properly tested fire door construction.

Also, please remember that not all fire doors are the same - so there's no single answer to this question! The first thing to check is the door manufacturer's test evidence for the door you have - whatever type and size (or sizes) of seal they have tested with is what you should buy.

Where door manufacturer's test evidence isn't available, the usual recommendation is to use a 15 x 4mm seal, fitted centrally at the head and both jambs or frame of a single leaf, single acting door. (If you are in any doubt, or have a particular application you would like to discuss, please contact our Technical Services team on 01626 834252 for details).

If it's a fire and smoke door (which will be denoted FD30S), then remember that a fire seal alone will not be sufficient. You should purchase a fire seal and a separate smoke seal or a combined fire and smoke seal, such as the Lorient DS.

Can you paint over fire and smoke seals?

Over-painting of fire seals should not compromise performance in a fire situation - however, **do not paint** over smoke seals as this will certainly compromise smoke containment performance. If the smoke seal part of the seal has already been painted over, you will need to replace the smoke seal. Our seals are available in a range of colours, plus woodgrain and metallic finishes, so over-painting should not be necessary. Guidance on the painting of seals maybe found in BS 8214:2016 Timber - based fire door assemblies - Code of practice. Section 14 outlines the situations in which over painting may be applied,

an extract from which is detailed below:

"Fire door leaves are generally not required to provide a specific surface spread-of-flame barrier, and may therefore be painted or lacquered as desired, in accordance with the manufacturer's recommendations where available.

Smoke-only seals should never be over painted. For combined intumescent fire and smoke seals, the smoke element should never be over painted. For intumescent fire-only seals, there is no evidence to suggest that over painting of intumescent fire seals has any detrimental effect on the ability of the seals to perform efficiently; however, over painting should be avoided wherever possible, or if unavoidable should be limited to a maximum of five coats of conventional paint or lacquer, or a maximum of 0.5 mm, whichever is the greater.

When preparing a frame for redecorating, the use of heat or chemical strippers should be avoided if seals are incorporated. If seals are damaged by either of these processes, they should be replaced in accordance with 13.2.3. Where glazing beads are identified as having been painted with intumescent paint, specialist advice should be obtained before repainting" BS 8214:2016"

What temperature do fire seals expand?

Sodium silicate intumescent material is activated at temperatures of between 100 - 150°C, forming a rigid foam with a high level of thermal insulation; it expands to 5 – 10 times its original size.

The intumescent material is activated at a much lower temperature than that at which the smoke seal material degrades. Long before the seal has burned away, the intumescent material has expanded sealing the gaps around the door. This seals the gap between the door and the frame, so providing an effective barrier to the passage of fire and hot smoke. For more specialised applications, we're able to utilise alternative intumescent core materials in our manufacturing process, or create bespoke sealing solutions. Please contact our Technical Services team for further information.

What is the recommended gap size at the threshold?

The gap at the bottom of a fire door should not be greater than 10mm, please refer to door manufacturers instructions for clarification.

Where fire and smoke containment is required BS 8214 states that the threshold of a fire and smoke door should not exceed **3mm** at any point; a smoke seal should be fitted at the threshold if the gap exceeds this.

What gaps are required between a fire door leaf and its frame?

The gap between the fire door and the frame is extremely important and must be suitable for the intumescent seal fitted.

The gap on a fire door should not exceed 2-4mm along the 2 long edges and head of the door leaf.

The gap on a fire and smoke door should not exceed 3mm along the 2 long edges and head of the door leaf.

I have an existing fire rated door, but I have been told that it needs to provide smoke containment too. What do you recommend?

The first product we would always recommend you consider is our Batwing[®] seal. With proven performance for acoustic and smoke containment, a choice of sizes for different sized door stops, and low frictional resistance for ease of door operation.



It fixes onto the doorstop with strong self-adhesive tape, it's easy to install and you won't need to remove your door to fit it.

Alternatively, another option is our range of architectural perimeter seals, which can be face-fixed to the door stop.

If you have double leaf doors, remember you will need to fit a seal at the meeting stile too.

And don't forget the threshold! It's essential to seal it for effective smoke containment. We have face-fixed options in both our door bottom seals and drop seals that can be installed without removing the door.

Do I need to fit a threshold plate?

A threshold plate is a good idea, for several reasons:

 It will help to ensure a good seal is maintained at the threshold, by giving a firm surface for a drop seal to rest against;

- It can help to prevent weather ingress when used as part of a storm-guard system (such as our LAS3008);
- If you are sealing dissimilar surfaces (eg, carpet and vinyl), the threshold plate can cover the join to prevent both wear and tripping hazards. Our threshold ramps can also easily accommodate differences in floor heights, to make access easier for all;
- If your floor surface is particularly liable to wear and tear in places below the door (eg, a high level of traffic, or over a carpet that may become compressed over time), then a threshold plate will help to prevent these uneven areas affecting the threshold seal.



Call our Technical Services team

+44 (0) 1626 834252

www.lorientuk.com







UK / EUROPE T: +44 (0) 1626 834252 E: sales@lorientuk.com

For further information about Lorient products please visit: www.lorientgroup.com

in

Þ

ሪ

/company/lorient

@lorientuk

@lorientuk

