

AAS 7506

AURA®

PERIMETER SEAL

A robust seal designed for use on plain or rebated meeting stiles. With proven acoustic performance it is also suitable for smoke, light, and draught containment. The leg can be cut out to make way for locks and latches.


MEDIUM DUTY



AAS7506 ↓



TECHNICAL



AAS7506 ↑

Location

Meeting stiles of single swing doors.
Double doors – where only one door leaf is in use

Seal Material

Co-extruded elastomeric with flexible curved fins

Standard Lengths

- 1m and 2.1m

Fixing

- Fixing holes pre-drilled and countersunk
- Wood screws supplied – please request self-tappers
- Using self-adhesive tape to position aluminium carrier while fixing, push-fit Batwing® seal into place

Note: A door selector should be considered unless one leaf is intended to be fixed

Finishes

- Silver or Bronze anodised aluminium
- Black, White, Dark Brown, Light Brown, Grey, Clear and Cream Batwing® inserts available

PERFORMANCE

Acoustic

BS EN ISO 10140-2: 2010

Weighted Sound Reduction Index

33 dB
(AAS7506 & AAS8501 on a standard architectural door)

Smoke Leakage

BS EN 1634-3: 2004
BS 476: Pt.31.1: 1983

Durability

1 million cycles on full-size door assemblies