

# AAS 7506

AURA®

## PERIMETER SEAL

*A robust seal designed for use on plain or rebated meeting stiles. With proven acoustic performance it is also suitable for smoke, light, and draught containment. The leg can be cut out to make way for locks and latches.*


### MEDIUM DUTY



AAS7506 ↓



### TECHNICAL



AAS7506 ↑

#### Location

Meeting stiles of single swing doors.  
Double doors – where only one door leaf is in use

#### Seal Material

Anodised aluminium carrier with co-extruded elastomeric insert with flexible curved fins

#### Standard Lengths

- 1m and 2.1m

#### Fixing

- Fixing holes pre-drilled and countersunk
- Wood screws supplied – please request self-tappers
- Using self-adhesive tape to position aluminium carrier while fixing, push-fit Batwing® seal into place

Note: A door selector should be considered unless one leaf is intended to be fixed

#### Finishes

- Silver anodised aluminium with grey insert as standard. Other finishes available to special order (non-standard - charges and lead times apply)
- Black, White, Dark Brown, Light Brown, Clear, Red, Silver and Cream Batwing® inserts are subject to MOQs

### PERFORMANCE

#### Acoustic

BS EN ISO 10140-2: 2010

#### Weighted Sound Reduction Index

33 dB

(AAS7506 & AAS8501 on a standard architectural door)

#### Smoke

BS EN 1634-3: 2004 & BS 476-31.1: 1983 at ambient temperature.

#### Durability

1 million cycles on full-size door assemblies