

FSR 5000

FACE-FIXED



A durable roller-type safety finger protector designed to prevent fingers becoming trapped on the non-hinge (cavity side) of single swing doors.

The tensioned roller mechanism maintains constant gasket pressure, creating a protective barrier between the door leaf and frame as the door opens and closes. The aluminium housing features adjustable fixing positions for accurate alignment during installation. The hard-wearing synthetic fibre gasket is fire retardant (B1 classified). Suitable for timber, metal, PVC and glass doors.



▲
FSR 5000



▲
FSR 5000

SYSTEM SPECIFICATIONS

Possible door types

- ▶ Suitable for doors made of wood, metal, PVC or glass.
- ▶ Suitable for manually operated and power operated doors.
- ▶ Single swing doors.

Location

- ▶ Planet finger protection FSR is fitted on doors to protect the push side on the side closing edge.

Seal material

- ▶ Carrier: aluminium.
- ▶ Gasket: Synthetic fibre.

Gasket size

- ▶ 260mm as standard.
- ▶ Other lengths to special order.

Lengths

- ▶ 1925mm as standard.
- ▶ 2015mm as standard for automatic doors.
- ▶ Other lengths to special order.
- ▶ Maximum length: 2500mm.
- ▶ Minimum length: 310mm.
- ▶ Please note: These seals must be ordered at the required length, as they cannot be cut down.

Fixing

- ▶ Self-tapping wood screws are supplied as standard (self-drilling screws for metal doors available on request).
- ▶ Fixing holes are pre-drilled to allow straightforward installation and accurate positioning of the seal on the door and frame.

Finishes

- ▶ Silver anodised aluminium with black gasket as standard.
- ▶ Matt black, white, grey, anthracite, stainless steel, and RAL carriers available to special order (non-standard - charges and lead times apply).
- ▶ Grey, white, red, blue, yellow gaskets are available to special order (non-standard - charges and lead times apply).





FSR 5000

HOW TO ORDER

SILVER ANODISED

ANTHRACITE

Length	Gasket	Order code	Order code
1925mm	Black	PLAF-5111	PLAF-5141
2015mm	Black	PLAF-5112	PLAF-5142
Made to measure	Black	PLAF-5113	PLAF-5143

Optional accessories	Detail	Use with	Item No.	Order Code
	Installation aid, with 6 adhesive pads	FSR 6000 FSR 5000	901320	PLA901320
	Hex pin wrench for roller protector, 2 x 20 x 50mm	FSR 6000 FSR 5000	901322	PLA901322
	Screws for roller protector FSR 6000, 10 pcs each/type of screw	FSR 6000 FSR 5000	901324	PLA901324
	Planet marking aid, plastic, black, set incl. pencil	FSR 6000 FSR 5000	901300	PLA901300