


FINESSE™ SEALS

LP1504 Finesse™, LP2004 Finesse™ 39dB


The Finesse™ seal offers the ultimate in acoustic, smoke + fire protection with the added benefit of thermal containment. This high-class seal offers performance and durability with a truly superb appearance. With clear fins as standard, it's ideal for luxury installations, where aesthetics are paramount. The seal also features antimicrobial protection and is available in a range of sizes to cover 30 and 60 minute applications.



ACOUSTIC, SMOKE + FIRE SEALS



LP1504 Finesse™



LP2004 Finesse™



Finesse™ (Shown with LAS8001 si + LAS4001)

SYSTEM SPECIFICATIONS

Test evidence

- ▶ Acoustic: BS EN ISO 10140-2: 2010 (up to Rw 39dB).
- ▶ Smoke: BS 476-31.1: 1983.
- ▶ Fire: BS 476-20/22: 1987 & BS EN 1634-1: 2014.
- ▶ Durability: 1 million cycles.

Performance

- ▶ Protects against sound, smoke, and fire.
- ▶ Thermal containment.
- ▶ Suitable for wheeled traffic.
- ▶ Exceptionally low frictional resistance for ease of door operation (Approved Document M).
- ▶ Integral antimicrobial protection.

Location

- ▶ Single and double leaf doors.

Size

- ▶ 15 x 4mm.
- ▶ 20 x 4mm.

Use with

- ▶ Any architectural seals.

Min/max gap size

- ▶ 3mm/4mm.

Seal material

- ▶ PVC encased sodium silicate and flexible elastomeric fins (4mm).

Standard lengths

- ▶ 1m and 2.1m.
- ▶ Other lengths to special order.

Fixing

- ▶ Heavy duty self-adhesive backing tape.

Finishes

- ▶ Available in a range of standard colours, plus woodgrain and metallic finishes, available to special order.
- ▶ Its transparent fin construction provides a virtually invisible fitted product - ideal for upgrading doorsets in heritage projects. Other fin colours are available to special order.

Accreditations



(CF330 & CF341)