


## COMPRESSION SEALS

# LAS1046

Superior quality, self-adhesive profile for door and window frames, which provides an acoustic compression seal. Lightweight and flexible. Quick and easy installation.



COMPRESSION SEALS



LAS1046



LAS1046

### SYSTEM SPECIFICATIONS

#### Performance

- ▶ Smoke seal for fire doors.
- ▶ Protects against sound, weather, draught and light.

#### Location

- ▶ Mounted on doorstep for single swing doors.

#### Use with

- ▶ Practically any threshold seal.

#### Min/max gap size

- ▶ 3mm/5mm.

#### Seal material

- ▶ Silicone.

#### Standard lengths

- ▶ 100m reels.

#### Fixing

- ▶ Self-adhesive tape.
- ▶ Note: contact surfaces must be clean, smooth and, if painted, well cured.

#### Colours

- ▶ White, dark brown or black.

#### Accreditation

- ▶ Positive pressure tested gasketing materials for fire doors. Intended application to listed steel frames and/or classified steel covered composite, hollow metal doors rated up to 3 hours. Also classified gasketing materials for fire rated doors intended for wood and plastic covered composite doors rated up to 1.5 hours and wood core doors rated 20 min. Category J, R25667.



3NLW

LAS1046

Dark brown & black