



#### CONTENTS LAS1206K Batwing<sup>®</sup>

#### TOOLS REQUIRED

- Tape measure
- Pencil or marker
- Mitre saw or snips

#### DISCLAIMER

Recommendations as to methods, use of materials and construction details are based on the experience and knowledge of Lorient and are given in good faith as a general guide and service to designers, contractors and manufacturers.

Lorient reserves the right to make alterations or delete any installation detail without prior notice.

## **INSTALLATION DETAIL**

#### IMPORTANT INFORMATION

Batwing<sup>®</sup> needs to have a 2-4 mm gap between the door and the door stop to enable the door to close. Tight gaps will dislodge the seal from its position.

It is essential to ensure that freshly painted surfaces are fully dry and cured before commencing installation.

#### STEP 1

Remove Batwing<sup>®</sup> from packaging and trim to length using snips.

#### STEP 2

Push fit seal into a into a 3mm wide x 11mm deep groove either in the corner of the frame or within the back edge of the doorstop, ensuring a tight jointing method at the top corner to ensure continuity of seal.

#### STEP 3

Run finger down centre of the profile pushing it into the centre of the reveal.

Ensure that the installation of this product does not impede the opening or closing of the door. It is recommended to check the door seal periodically to ensure the door assembly to which it is fitted, closes and latches properly.





Gasketing materials for fire doors intended for application to wood and plastic covered composite and wood core doors rated up to 1.5 hours. Listed steel frames and/or classified steel covered composite, hollow metal doors rated up to 3 hours.

V4

# 

### ASSA ABLOY

ASSA ABLOY LTD T/A LORIENT Endeavour House Fairfax Road Heathfield Ind Estate Newton Abbot Devon TQ12 6UD United Kingdom

> +44 (0)1626 834252 www.lorientgroup.com

All rights reserved. No part of this fitting guide may be reproduced, stored in a retrieval system, or transmitted in any means, electronic, mechanical, photocopying, recording or otherwise without the written permission of Lorient. © 2024 ASSA ABLOY Ltd T/A Lorient. Lorient is a registered trade mark of ASSA ABLOY LIMITED in England.

For more information please call: +44 (0)1626 834252