

## PERIMETER SEALS


# LAS1206K + LAS1212K Batwing® on-a-stick

MEDIUM DUTY **37dB**

Medium duty, acoustic and smoke perimeter seals; which minimise the opening and closing resistance of the door leaf due to their unique, curved fins. Flexible elastomeric fin material springs back to original shape to provide ongoing performance and durability in service. They can be fitted with minimal disruption to the door assembly.



PERIMETER SEALS



▲ LAS1206K  
Batwing®  
on-a-stick

▲ LAS1212K  
Batwing®  
on-a-stick



▲ LAS1206K Batwing®

## SYSTEM SPECIFICATIONS

### Test evidence

- ▶ Acoustic: BS EN ISO 10140-2: 2010 (up to Rw 37dB).
- ▶ Smoke: BS 476-31.1: 1983 at ambient temperature; effective smoke seal up to 200°C.
- ▶ Durability: minimum of 100,000 cycles.

### Performance

- ▶ Meets smoke requirement: BS 9999: 2017.
- ▶ Protects against sound, smoke, draught and light.

### Location

- ▶ Head and jambs of single and double leaf doors.

### Use with

- ▶ Practically any drop seal.

### Min/max gap size

- ▶ 3mm/4mm.

### Seal material

- ▶ Co-extruded rigid back PVC with flexible fins.

### Standard lengths

- ▶ 1m and 2.1m.
- ▶ Single doorset pack consisting of 1 x 1m and 2 x 2.1m.
- ▶ Other lengths to special order.

### Fixing

- ▶ Supplied with strong self-adhesive tape, tested on many surfaces, including

MDF – suitable for internal use only.

- ▶ Groove size for LAS1212K is 9mm x 3mm – suitable for internal or external use.

### Colours

- ▶ Black, white, dark brown, light brown, grey, silver, cream, red and clear.
- ▶ Note: clear Batwing® will not prevent light penetration.

### Accreditations



(R27972)



(CF5179)  
LAS1212K

