

LAS3006 DOOR BOTTOM SEAL

FITTING GUIDE



LENGTH

CONTENTS LAS3006 door bottom seal

TOOLS REQUIRED

- Tape measure
- Pencil or marker
- Router with 3mm cutter
- Scissors, knife or snips

NOTE

Lorient reserves the right to make alterations or delete any installation detail without prior notice.

INSTALLATION DETAIL

STEP 1

Remove the seal from the packaging and measure the door width to determine the seal length required. Cut length to suit door bottom.

STEP 2

Groove the door bottom 3mm wide x 7mm deep.

STEP 3 Push fit the LAS3006 product into the groove.

NOTE

Do not install this product to impede the opening or closing of the door. It is recommended to check the adjustment of the door seal periodically to insure the door assembly closes and latches properly, whether or not equipped with a closing device.



V1

Lorient Pacific Ltd Unit A2, 5/F Wing Tai Centre 12 Hing Yip Street Kwun Tong Hong Kong

> +852 2505 0328 www.lorienthk.com

All rights reserved. No part of this fitting guide may be reproduced, stored in a retrieval system, or transmitted in any means, electronic, mechanical, photocopying, recording or otherwise without the written permission of Lorient Polyproducts Ltd 2019 © Lorient Polyproducts Ltd 2019

For more information please call:

+852 2505 0328