

# LAS3006 DOOR BOTTOM SEAL

## **FITTING GUIDE**



LENGTH

### CONTENTS

. LAS3006 door bottom seal

### **TOOLS REQUIRED**

- Tape measure
- Pencil or marker
- Router with 3mm cutter
- Scissors, knife or snips

### NOTE

Lorient reserves the right to make alterations or delete any installation detail without prior notice.

### INSTALLATION DETAIL

### STEP 1

Remove the seal from the packaging and measure the door width to determine the seal length required. Cut length to suit door bottom.

### STEP 2

Groove the door bottom 3mm wide x 7mm deep.

### STEP 3

Push fit the LAS3006 product into the groove.

### NOTE

Do not install this product to impede the opening or closing of the door. It is recommended to check the adjustment of the door seal periodically to insure the door assembly closes and latches properly, whether or not equipped with a closing device.







Lorient Gulf Building Materials Trading LLC PO Box 127987 Dubai, UAE

+9714 883 7206 www.lorientgulf.ae

All rights reserved. No part of this fitting guide may be reproduced, stored in a retrieval system, or transmitted in any means, electronic, mechanical, photocopying, recording or otherwise without the written permission of Lorient Polyproducts Limited.

© Lorient Polyproducts Ltd 2019