

DOOR BOTTOM SEALS


LAS3008 si

MEDIUM DUTY

A multi-blade, storm-proof seal combination consisting of the LAS3007 si door bottom seal and LAS4015 threshold plate. Durable, anodised aesthetic finish. It can be fitted without removing the door. Concealed fixings, pre-drilled and slotted holes on LAS3007 si for easy adjustment.



DOOR BOTTOM SEALS



LAS3008 si



SYSTEM SPECIFICATIONS

Performance

- ▶ Protects against smoke, weather, draught, light and insects when fitted with a suitable threshold seal.

Location

- ▶ Single swing doors.

Use with

- ▶ Practically any threshold plate.

Min/max gap size

- ▶ 26mm/32mm.

Seal material

- ▶ LAS3007 si – Flexible silicone rubber.
- ▶ LAS4015 – Aluminium with PVC cover strip.

Standard lengths

- ▶ 1m and 2.1m. Other lengths to special order.

Fixing

- ▶ LAS3007 si – Self-tapping wood screws are supplied (self-drilling and self-tapping screws for metal construction available on request). Fixing holes are predrilled and slotted to allow the seals to be adjusted and positioned accurately.
- ▶ A PVC cover strip to conceal fixings is supplied.
- ▶ LAS4015 – Fixing screws are supplied. PVC cover strip to conceal fixings is supplied.

Finishes

- ▶ LAS3007 si – Silver anodised aluminium with grey cover strip and grey silicone rubber gasket.
- ▶ LAS3007 si – Bronze anodised aluminium with black cover strip and black silicone rubber gasket.
- ▶ LAS4015 – Silver anodised aluminium with grey cover strip or bronze anodised aluminium with black cover strip.