


DOOR BOTTOM SEALS

LAS3008 si

FACE-FIXED

A multi-blade, door bottom seal combination consisting of the LAS3007 si door bottom seal and LAS4015 threshold plate. Durable, anodised aesthetic finish. It can be fitted without removing the door. Concealed fixings, pre-drilled and slotted holes on LAS3007 si for easy adjustment.



LAS3008 si



LAS3008 si

SYSTEM SPECIFICATIONS

Characteristics

- Contributes towards smoke, weather, draught, and light containment.

Location

- Single swing doors.

Min/max gap size

- 26mm/32mm.

Seal material

- LAS3007 si – Aluminium carrier with a flexible silicone rubber gasket.
- LAS4015 – Aluminium with PVC cover strip.

Standard lengths

- 1m and 2.1m. Other lengths to special order.

Fixing

- LAS3007 si – Self-tapping wood screws are supplied (self-drilling and self-tapping screws for metal construction available on request). Fixing holes are predrilled and slotted to allow the seals to be adjusted and positioned accurately.
- A PVC cover strip to conceal fixings is supplied.
- LAS4015 – Fixing screws are supplied. PVC cover strip to conceal fixings is supplied.

Finishes

- Silver anodised aluminium with grey cover strip and grey silicone rubber blade.
- Bronze anodised aluminium with black cover strip and black silicone rubber blade are subject to non-standard charges and additional lead times.