


DOOR BOTTOM SEALS

LAS3009 si

MORTISED

The LAS3009 si door bottom seal is a practical and efficient solution designed to contribute to the sound and environmental containment of your door. Equipped with two durable silicone blade seals, it forms a reliable barrier that helps reduce sound, smoke, draughts, and light—creating a quieter and more comfortable space. Suitable for single and double swing doors, as well meeting stiles (one leaf only).



LAS3009 si



LAS3009 si (shown with LAS4002)

SYSTEM SPECIFICATIONS

Characteristics

- ▶ Contributes towards smoke, weather, draught, and light containment when fitted with a suitable threshold seal.

Location

- ▶ Single and double swing doors.

Use with

- ▶ Practically any threshold plate.

Min/max gap size

- ▶ 16mm/22mm.

Seal material

- ▶ Flexible silicone rubber.

- ▶ 1m and 2.1m. Other lengths to special order.

Fixing

- ▶ Self-tapping wood screws are supplied (self-drilling and self-tapping screws for metal construction available on request).
- ▶ Fixing holes are pre-drilled. Once the aluminium carrier is fixed, the rubber gasket slides easily into place.
- ▶ Note: these seals cannot be adjusted once fitted.

- ▶ Silver anodised aluminium with grey silicone rubber blades.
- ▶ Bronze anodised aluminium with black silicone rubber blades are subject to non-standard charges and additional lead times.

Specification



NBS Source
PARTNER

Standard lengths

Finishes