


## DOOR BOTTOM SEALS


# LAS3050

## HEAVY DUTY

A durable door bottom seal with a grade 304 stainless steel fixing plate. Low maintenance and extremely resistant to weathering or aggressive commercial environments. Impervious to most chemicals, solvents, cleaning fluids and disinfectants. Quick and easy installation.



DOOR BOTTOM SEALS



▲ LAS3050



▲ LAS3050 (shown with LAS4050)

### SYSTEM SPECIFICATIONS

#### Performance

- ▶ Protects against smoke, weather, draught, light and insects when fitted with a suitable threshold seal.

#### Location

- ▶ Single and double leaf doors.
- ▶ Up and over garage doors.
- ▶ Roller shutter doors.

#### Use with

- ▶ Any stainless steel threshold plate.

#### Min/max gap size

- ▶ 5mm/10mm.

#### Seal material

- ▶ Foamed silicone rubber.

#### Standard lengths

- ▶ 1m and 2.1m. Other lengths to special order.

#### Fixing

- ▶ Fixing screws are supplied, fixing holes are pre-drilled and slotted to allow the seals to be adjusted and positioned accurately.

#### Finishes

- ▶ Brushed stainless steel with grey silicone rubber.
- ▶ Polished stainless steel (non-standard - charges and lead times apply).