


LAS3050 DOOR BOTTOM SEAL

FITTING GUIDE



LENGTH _____

CONTENTS

- LAS3050 door bottom seal
- Bag of screws

TOOLS REQUIRED

- Tape measure
- Pencil or marker
- Saw, hand or power
- Screwdriver, hand or power
- Drill
- 2.5mm drill bit

For more information please call:

+9714 883 7206

INSTALLATION DETAIL

STEP 1

Remove from packaging and measure length against height/width of door.

STEP 2

Measure and cut gasketing material to the exact length required for the opening. Cut stainless steel holder to size using a saw.

STEP 3

Position LAS3050 at the bottom of the door. Close door. Tap door seal down until desired contact is made between seal and threshold.

STEP 4

Mark hole locations with a punch or other marking tool.

STEP 5

Drill pilot holes for each screw using a 2.5mm drill bit.

STEP 6

Screw fix using screws supplied (fixing holes are pre-drilled and slotted to enable the seal to be fitted accurately and adjusted as required).

NOTE

We recommend the LAS3050 door bottom seal to be used together with a LAS threshold plate.

NOTE

Do not install this product to impede the opening or closing of the door. It is recommended to check the adjustment of the door seal periodically to insure the door assembly closes and latches properly, whether or not equipped with a closing device.



NOTE

Lorient reserves the right to make alterations or delete any installation detail without prior notice.

V1