


MAGNETIC SEALS

LAS6001

FACE-FIXED 40dB

A refrigeration-type vinyl magnetic strip in anodised aluminium housing. The strip holds the door closed so latches are not always required. Concealed fixings, pre-drilled and slotted holes for easy adjustment. Easily installed without removing the door and it can be used as a stop. Option to be supplied with magnetic keeper strip.



▲
LAS6001



▲
LAS6011



SYSTEM SPECIFICATIONS

Test evidence

- ▶ Acoustic: BS EN ISO 10140-2: 2010 (up to Rw 40dB).

Characteristics

- ▶ Contributes towards sound, smoke weather, draught, and light containment.

Location

- ▶ Head and jambs of single swing steel clad doors and timber doors (use with LAS6011).

Seal material

- ▶ LAS6001 – flexible insert with magnetic core.
- ▶ LAS6011 – PVC sleeve with magnetic insert.

Standard lengths

- ▶ 1m and 2.1m. Other lengths to special order.
- ▶ Subject to MOQs.

Fixing

- ▶ Self-tapping wood screws are supplied (self-drilling and self-tapping screws for metal construction available on request).
- ▶ Fixing holes are pre-drilled and slotted to allow the seals to be adjusted and positioned accurately. A PVC cover strip to conceal fixings is supplied.
- ▶ LAS6011 has an aggressive self-adhesive backing for fixing into a groove on timber doors.
- ▶ Note: order LAS6011 magnetic keeper strip for use with timber doors. Supplied with self-adhesive backing as standard.

Finishes

- ▶ LAS6001 – silver anodised aluminium with grey insert as standard.
- ▶ LAS6011 – white, black, grey, light brown, dark brown PVC sleeve. Other colours to special order subject to MOQs.