


# LAS6002

## MAGNETIC SEAL

### FITTING GUIDE



#### CONTENTS

- LAS6002 magnetic seal

#### TOOLS REQUIRED

- Tape measure
- Pencil or marker
- Power saw
- Router

#### NOTE

Recommendations as to methods, use of materials and construction details are based on the experience and knowledge of Lorient and are given in good faith as a general guide and service to designers, contractors and manufacturers.

Lorient reserves the right to make alterations or delete any installation detail without prior notice.

For more information please call:

**+44 (0)1626 834252**

## INSTALLATION DETAIL

#### NOTE

Check the magnetic attraction of the LAS6002 before cutting the seal to lengths required to ensure they attract and not repel.

For efficient operation a uniform gap of 5-7mm is required between door leaves.

#### STEP 1

Remove the seal from the packaging, and measure the height of the meeting stile.

#### STEP 2

Remove the door from its hinges and using a router create a 12mm deep x 16mm wide groove in the edge of the timber door. **The seal is not suitable when centre latching is required.**

#### STEP 3

Cut the carrier, gasket and magnet to the length required, take care to neatly cut the profile with a power saw.

#### STEP 4

Insert the LAS6002 into the groove. The aluminium trough section is toothed and splayed to lock into groove – no fixings are required.

#### STEP 5

Re-hang the door onto its hinges & ensure seal is clean.

#### STEP 6

Close the door and ensure the seal makes uniform contact with the opposite door leaf. Repeat steps 1-5 to install the opposite seal.

#### NOTE

Initial contact of seals may take several seconds, subsequent connections are immediate.

#### NOTE

Ensure that the installation of this product does not impede the opening or closing of the door. It is recommended to check the door seal periodically to ensure the door assembly to which it is fitted, closes and latches properly.

Periodic inspection and cleaning is recommended to fully maintain this sealing system. Normally an annual inspection is sufficient. For smoke sealing applications, refer to local regulatory authority standards.



#### NOTE

We recommend the LAS6002 magnetic seal is fitted with the LAS8001 si or LAS8006 si drop seal, a Lorient perimeter seal and, if required a threshold plate.

V1



Lorient Polyproducts Ltd  
Endeavour House  
Fairfax Road  
Heathfield Ind Estate  
Newton Abbot  
Devon TQ12 6UD  
United Kingdom

+44 (0)1626 834252  
[www.lorientgroup.com](http://www.lorientgroup.com)

All rights reserved. No part of this fitting guide may be reproduced, stored in a retrieval system, or transmitted in any means, electronic, mechanical, photocopying, recording or otherwise without the written permission of Lorient Polyproducts Limited.  
© Lorient Polyproducts Ltd 2019