


PERIMETER SEALS

LAS7002 si

FACE-FIXED **34dB**

Slimline aluminium perimeter seal featuring a silicone gasket, ideal for smoke and acoustic containment. Designed to be fitted to existing door stops, it is suitable for timber door assemblies. A neat cover plate conceals fixing screws, and it can be easily installed without removing the door.



LAS7002 si



LAS7002 si

SYSTEM SPECIFICATIONS

Test evidence

- ▶ Smoke: BS 476-31.1:1983 at ambient temperature.
- ▶ Acoustic: BS EN ISO 10140-2: 2010. si (up to R_w 34dB).
- ▶ Durability: 100,000 cycles.

Characteristics

- ▶ Contributes towards sound, smoke, draught, weather, and light containment.

Location

- ▶ Head and jambs of single swing doors.

Use with

- ▶ Practically any threshold seal.

Seal material

- ▶ Flexible silicone rubber.

Standard lengths

- ▶ 1m and 2.1m. Single doorset pack consisting of 1 x 1m and 2 x 2.1m. Other lengths to special order.

Fixing

- ▶ Self-tapping wood screws are supplied (self-drilling and self-tapping screws for metal construction available on request).
- ▶ Fixing holes are pre-drilled and slotted to allow the seals to be adjusted and positioned accurately. A PVC cover strip to conceal fixings is supplied.

Finishes

- ▶ Silver anodised aluminium with grey cover strip and grey silicone rubber gasket as standard.
- ▶ Other powder-coated carrier finishes are subject to non-standard charges, MOQS and additional lead times.

Certification

certifire
(CF5179)

