


LAS7005 si

FACE-FIXED **31dB**

A neat, aesthetically designed, compact perimeter seal with proven effective acoustic performance. Decorative cover strip conceals fixings. This seal can be used to replace the stop on steel or timber framed doors. To avoid excessive impact on the seal we recommend using a door closer to aid closing control.



▲ LAS7005 si



▲ LAS7005 si

SYSTEM SPECIFICATIONS

Test evidence

- Acoustic: BS EN ISO 10140-2:2010 (up to Rw 31dB).

Characteristics

- Contributes towards sound, smoke, draught, weather, and light containment.

Location

- Head and jambs of single swing doors.

Use with

- Practically any threshold seal.

Seal material

- Flexible silicone rubber.

Standard lengths

- 1m and 2.1m. Single doorset pack consisting of 1 x 1m and 2 x 2.1m.
- Other lengths to special order.

Fixing

- Self-tapping wood screws are supplied (self-drilling and self-tapping screws for metal construction available on request)
- Fixing holes are pre-drilled and slotted to allow the seals to be adjusted and positioned accurately. A PVC cover strip to conceal fixings is supplied.

Finishes

- Silver anodised aluminium with grey cover strip and grey silicone rubber gasket as standard.
- Bronze anodised aluminium with black cover strip and black silicone rubber gasket or other powder-coated colour finishes are subject to non-standard charges and additional lead times.