

## MEETING STILE SEAL


# LAS7006 si

## FACE-FIXED

A high performance seal designed for use on plain or rebated meeting stiles. With proven medium temperature smoke performance, it also makes a positive contribution to light, sound, and draught containment. The leg can be cut out to make way for locks and latches.



MEETING STILE SEAL



▲ LAS7006 si



▲ LAS7006 si

## SYSTEM SPECIFICATIONS

### Test evidence

- ▶ Medium Temp Smoke Leakage: BS EN 1634-3: 2004 (S<sub>200</sub>).

### Performance

- ▶ Protects against smoke, sound draught, dust, light and weather.

### Location

- ▶ Meeting stiles of single swing doors.
- ▶ Double doors – where only one door leaf is in use or a door selector is fitted.

### Use with

- ▶ Practically any perimeter seal.

### Seal material

- ▶ Aluminium carrier with flexible silicone blade.

### Standard length

- ▶ 2.1m.

### Fixing

- ▶ Secure with heavy duty self-adhesive tape.
- ▶ Screw into place (fixings supplied).
- ▶ Note: A door selector should be considered unless one leaf is intended to be fixed.

### Finishes

- ▶ Silver anodised aluminium with grey silicone rubber gasket as standard.
- ▶ Other finishes available to special order (non-standard – charges and lead times apply).