

## AIR TRANSFER GRILLES

# LVN25

### HIGH PERFORMANCE NON-VISION STYLE INTUMESCENT AIR TRANSFER GRILLE

The LVN25 is a non-vision intumescent air transfer grille supplied in two halves to accommodate door thicknesses up to 50mm. When finished with a colour co-ordinated edge flange, it results in an attractive but efficient air transfer feature.

#### Key benefits

- ▶ Louvred slats give privacy
- ▶ Bi-directional airflow
- ▶ No site testing necessary
- ▶ No moving parts
- ▶ Attractive facade on both sides
- ▶ Colour match available
- ▶ Easy to keep clean.

#### STANDARD SIZES AVAILABLE (MM)

WIDTH	98	148	198	248	298	348	398	448	498	598
HEIGHT	98	148	198	248	298	348	398	448	498	598

Other non-standard sizes may be available - please ask for details.



↑  
LVN25

#### SYSTEM SPECIFICATIONS

##### Test evidence

- ▶ Fire: BS 476-20 & 22:1987.

##### Performance

- ▶ Can be used to provide up to 60 minutes resistance to fire.

##### Size

- ▶ Width: 100mm - 600mm (in 50mm increments).
- ▶ Height: 100mm - 600mm (in 50mm increments).

##### Thickness

- ▶ 2 pieces x 25mm.

##### Free area

- ▶ Approx 30% free area.

##### Material

- ▶ Rigid PVC slats with an intumescent core

##### Application

- ▶ Suitable for doors of minimum 50mm thickness.
- ▶ Note: in applications where high levels of humidity or wetness are anticipated, it is recommended that an LVH44 product should be employed.

##### Orientation

- ▶ LVN25 is best suited in the vertical plane.

##### Positional requirements (Certifire)

- ▶ The upper edge of the grille shall be no higher than 800mm from floor level.

##### Finish

- ▶ Silver as standard.

##### Fixing

- ▶ Each air transfer grille is manufactured 2mm less than a nominal aperture size to provide clearance when installed in a duct or other aperture of the same nominal dimensions. E.g. a 198mm x 198mm nominal size damper will suit a 200mm x 200mm aperture.
- ▶ Screwed and bedded in Lorient intumescent sealant.

##### Use with

- ▶ Integral steel or aluminium flanges.
- ▶ No cover grille required.

##### Certification

(CF564)