
Planet KG-SM Set Narrow



FACE-FIXED



A slimline, face-fixed automatic drop seal designed for glass, timber, metal, and PVC doors. Its ultra-narrow 11.5mm profile makes it ideal for minimalistic applications. Featuring a high-efficiency mechanism with a single-sided trigger, it enables parallel lowering and automatic compensation for sloping floors. Suitable for doors with a seal height of up to 16mm. Fixing tape allows for quick and easy installation on new and existing doors. An optional bevel lip is available for uneven floors, accommodating gaps of up to 20mm.





Planet KG-SM Set Narrow

Planet KG-SM Set Narrow Drop Seal

SYSTEM SPECIFICATIONS

Key benefits

- Elegant architectural design solution.
- For new and existing doors.
- > Unilateral and silent actuation.
- No scraping / trailing on the floor, thanks to parallel drop.
- High-quality silicone lip, lateral protrusion adjustable.
- Can be shortened to the next smaller stock length.

Characteristics

- Suitable for use on glass, timber, metal & PVC doors.
- Sound absorption level up to 48dB (at ground air 7 mm).

Possible door types (depending on options)

Single swing doors, double swing doors, sliding doors.

Profile size

▶ 11.5mm x 38mm.

Max drop height

▶ 16mm.

Profile material

Aluminium.

Seal material

- Planet KG-SM set narrow RD: High-quality silicone.
- Planet KG-SM set narrow FH+RD: Highquality self-extinguishing silicone with aluminium carrier.
- Bevel lip available for uneven floors (Left-handed or right-handed variants.

Adjustment

- Self-levelling on uneven surfaces.
- > Automatic compensation of sloped floors.
- Easy drop height adjustment.
- Door bottom can be adjusted without seal removal.

Drop height adjustment

Using 3mm allen key.



- 459mm, 584mm, 709mm, 834mm, 959mm, 1084mm, 1209mm, 1334mm, 1459mm.
- Note: Each length can be cut back by 125mm.
- Sizes up to 6m are available to special order.

Fixing

• Glued to the side with double adhesive tape (supplied).

Accessories (supplied)

 Complete set consisting of drop-down seal, protection profile with prepared double adhesive tape, cover plates, stopping plates, fixing screws, optical film, Allen key.

Finishes

- Silver anodised EV1 as standard.
- Matt anodised stainless steel (INOX) or black C35 matt anodised or special colours powder coated (RAL / DB / NCS) to special order.



T: +44 (0)1626 834252 E: mktg@lorientuk.com www.lorientuk.com