


# SYSTEM-36/10 PLUS

FD30


System-36/10 PLUS is a flexible U-shaped glazing gasket designed for 30 minutes fire resistance in doors and screens. Flexible enough to be fitted to curved corners and circular vision panels. Tested with many popular glass types. Supplied coiled in a box so it's easily dispensed and cut to length, reducing wastage.



FIRE RESISTANT GLAZING SYSTEMS




SYSTEM-36/10 PLUS



LG1521

For 44mm thick doors or rebated screen frames.



LG1520

For unrebated screen frames.



## SYSTEM SPECIFICATIONS

### Test evidence

- ▶ Fire: BS EN 1634-1: 2014.
- ▶ Fire: BS 476-22: 1987.

### Performance

- ▶ Provides 30 minutes fire resistance.

### Size

- ▶ 16mm x 17.5mm.

### Standard lengths

- ▶ 30m coils.

### Seal material

- ▶ Sodium silicate intumescent.

### Finish

- ▶ Black with green identification spine.

### Glass thickness

- ▶ Suitable for use with 9mm - 11mm fire rated glass.

### Glass type

- ▶ Please refer to Certifire certificate CF5060 for the full range of glass types.

### Application

- ▶ Doors and screens.
- ▶ FD30 fire doors.

### Intumescent liner

- ▶ Liner is required for flaxboard substrates below 500kg/m<sup>3</sup>.

### Glazing beads

- ▶ Glazing beads are required on both sides of the glass.
- ▶ Note: Hardwood or softwood beads are available (min density 550kg/m<sup>3</sup>).
- ▶ Fixing of beads: Screwed using No.8 x 45mm countersunk screws at 200mm nom. centres.

### Accreditation

